




雷射LED

詳細產品規格-請點擊www.100y.com.tw



- Features**
- Cost effective
 - High precision assembly
 - High visibility

- Applications**
- General purpose red laser light source
 - Industrial laser markers / measuring instruments
 - Laser pointers / levelers



| Part No. | Product No. | 製造廠商 | 說明 | 功率輸出 Po (mW) | 波長 λP(nm) | 光束發 θ/θL (deg) | 監控電流 Im(uA) | Package | 工作溫度 (°C) | 工作電流 Iop(mA) |
|----------|---------------|------------|--------|--------------|-----------|----------------|-------------|---------|---------------|--------------|
| 62572 | ADX-6305STL-5 | Arima Opto | 雷射 LED | 5mW | 635nm | 7.5deg / 33deg | 0.15mA | TO-18 | -10°C ~40°C | 33mA |
| 59098 | ADX-6305STU | Arima Opto | 雷射 LED | 5mW | 635nm | 7.5/33 | 0.15mA | TO-18 | -10°C ~ +40°C | 33mA |



| Part No. | Product No. | 製造廠商 | 說明 | 功率輸出 Po (mW) | 波長 λP(nm) | 光束發 θ/θL (deg) | 監控電流 Im(uA) | Package | 工作溫度(°C) | 工作電流 Iop(mA) |
|----------|-------------|------------|--------|--------------|-----------|----------------|-------------|---------|----------|--------------|
| 29049 | ELD65A5-1 | Arima Opto | 雷射 LED | 5mW | 650nm | 8/38 | 100uA | TO-18 | -10~50°C | 20mA |
| 27364 | EL65-18-A | EVERLIGHT | 雷射 LED | 5mW | 650nm | 8/35deg | 300uA | TO-18 | -10-40°C | 25mA |



| Part No. | Product No. | 製造廠商 | 說明 | 功率輸出 Po (mW) | 波長 λP(nm) | 光束發 θ/θL (deg) | Package | 工作溫度 (°C) | 工作電流 Iop(mA) |
|----------|------------------|-----------|--------------------------|--------------|-----------|----------------|---------|-----------|--------------|
| 39073 | HLDH-650-A-10-01 | HUEY JANN | Laser LED | 10mW | 650nm | 9/28 | TO-18 | -10~50°C | 26 |
| 39074 | HLDH-660-A-20-01 | HUEY JANN | Laser LED | 20mW | 650nm | 8/16 | TO-18 | -10~60°C | 80 |
| 58606 | HLDH-780-A-90-02 | HUEY JANN | Laser LED(For CD player) | 90mW | 785nm | 9/17 | TO-18 | -10~70°C | 115 |



| Part No. | Product No. | 說明 | 功率輸出 Po (mW) | 波長 λP(nm) | 光束發 θ/θL (deg) | 監控電流 Im(uA) | Package | 工作溫度 (°C) | 工作電流 Iop(mA) |
|----------|-----------------------|--------|--------------|-----------|----------------|-------------|---------|-----------|--------------|
| 30619 | LD-650-5mW-A-90-260uA | 雷射 LED | 5mW | 650nm | 7/38 | 90-260uA | TO-18 | -10~40°C | 18mA |

光射式開關元件+Amp
光纖感測開關元件


詳細產品規格-請點擊www.100y.com.tw



- Ensures a sensing distance approximately 1.5 to 2 times larger than that of any conventional OMRON sensor
- Problems such as the collision of workpieces are eliminated
- Full range of standard sizes(M8, M12, M18 and M30; both long and short barrels)
- Modular construction simplifies customization



| Part No. | Product No. | 製造廠商 | 說明 | 供應電壓 | Output | LED | Angle |
|----------|-------------------|-------|---------------------|----------|-------------|-------|-------|
| 62182 | E2A-M12KN08-WP-C1 | OMRON | OMRON_圓柱形接近傳感器 | 12-24VDC | 200mA/32VDC | - | NPN |
| 58035 | E2A-S08KS02-WP-B1 | OMRON | Special-Purpose 感測器 | 12-24VDC | 200mA/32VDC | 2.0mm | PNP |
| 58034 | E2A-S08KS02-WP-C1 | OMRON | Special-Purpose 感測器 | 12-24VDC | 200mA/32VDC | 2.0mm | PNP |



| Part No. | Product No. | 製造廠商 | 說明 | 檢測距離 | 最小值測的物体 |
|----------|--------------|-------|-----------|---------|------------|
| 53066 | E32-C31 | OMRON | 光纖管 | - | - |
| 51119 | E32-CC200-2M | OMRON | 光纖管 | 300mm | φ0.005mm |
| 51117 | E32-D32-2M | OMRON | OMRON_光纖管 | 75mm | φ0.005mm |
| 51121 | E32-D33-2M | OMRON | 光纖管 | 16mm | φ0.005mm |
| 50187 | E32-T24S | OMRON | 光纖管-透過型 | 1,300mm | φ2(φ0.1)mm |
| 51120 | E32-TC200-2M | OMRON | 歐姆龍光纖管 | 760mm | φ0.005 |



| Part No. | Product No. | 製造廠商 | 說明 | 檢測距離 | 最小值測的物体 |
|----------|-------------|-------|-----|----------|----------|
| 58033 | E32-C42 | OMRON | 光纖管 | 6mm~15mm | φ0.005mm |

