



300-600W 單組交換式電源供應器

詳細產品規格-請點擊www.100y.com.tw



- 特性**
- 國際通用全範圍交流輸入
 - 保護種類：短路/過負載/過電壓
 - 自然風冷
 - 安裝軌道：TS-35/7.5或TS-35/15
 - 絕緣等級：Class II
 - LED電源指示
 - 空載消耗<0.5W
 - 100%滿載老化測試

- 輸入電壓範圍：85~264VAC或120~370VDC
- 頻率範圍：47~63Hz
- 浪湧電流(Typ.): 冷啟動：35A/115VAC 65A/230VAC
- 交流電流(Typ.): 0.88A/115VAC 0.48A/230VAC
- 尺寸：25*93*56mm(W*H*D)



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
64612	DR-15-15	MEAN WELL	MEAN WELL_15W Single Output Class II DIN Rail Power	15V	1.0A	±1%



Part No.	Product No.	說明	Output Volt.	Output Current	Tol.(±)
65678	F-600-24	600W 電源供應器	600W	AC100V/AC200V	DC24V/25A



- 特性**
- 交流輸入範圍通過開關切換
 - 保護種類：短路/過負載/過電壓/過溫度
 - 內置直流風扇強制風冷
 - 冷卻風扇自動控制
 - 100%滿載老化
 - 開關工作頻率：90KHz

- 輸入電壓範圍：88~132VAC/176~264VAC(開關切換)或248~370VDC
- 頻率範圍：47~63Hz
- 交流電流(Typ.):6A/115VAC 3.5A/230VAC
- 浪湧電流(Typ.):18A/115VAC 36A/230VAC
- 漏電流：<3.5mA/240VAC
- 尺寸：215*115*50mm(L*W*H)



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
7539	S-320-5	MEAN WELL	交換式電源供應器	5VDC	50A	±2%
20974	S-320-7.5	MEAN WELL	交換式電源供應器	7.5Vdc	36A	±2%
7540	S-320-12	MEAN WELL	交換式電源供應器	12VDC	25A	±1%
20975	S-320-13.5	MEAN WELL	交換式電源供應器	13.5Vdc	22A	±1%
7541	S-320-15	MEAN WELL	交換式電源供應器	15VDC	20A	±1%
7542	S-320-24	MEAN WELL	交換式電源供應器	24VDC	12.5A	±1%
17592	S-320-27	MEAN WELL	交換式電源供應器	27Vdc	11A	±1%
7543	S-320-48	MEAN WELL	交換式電源供應器	48VDC	6.5A	±1%



- AC input range selectable by switch
- Protections: Short circuit / Overload / Over voltage
- Forced air cooling by built-in DC fan
- PWM control and regulated

- Built-in cooling Fan ON-OFF control
- 100% full load burn-in test
- Fixed switching frequency at 25KHz
- Low cost



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
20976	S-350-5	MEAN WELL	350W 交換式電源供應器	5VDC	50A	±2%
20977	S-350-7.5	MEAN WELL	350W 交換式電源供應器	7.5VDC	40A	±2%
14971	S-350-12	MEAN WELL	350W 交換式電源供應器	12Vdc	29A	±1%
20978	S-350-13.5	MEAN WELL	350W 交換式電源供應器	13.5VDC	25.8A	±1%
20979	S-350-15	MEAN WELL	350W 交換式電源供應器	15VDC	23.2A	±1%
12269	S-350-24	MEAN WELL	350W 交換式電源供應器	24Vdc	14.6A	±1%
20983	S-350-27	MEAN WELL	350W 交換式電源供應器	27VDC	13A	±1%
56430	S-350-36	MEAN WELL	350W 交換式電源供應器	36VDC	9.7A	±1%
20984	S-350-48	MEAN WELL	350W 交換式電源供應器	48VDC	7.3A	±1%



- 特性**
- 交流輸入電壓限制
 - 交流輸入範圍通過開關置換
 - 保護種類：短路/過負載/過電壓/過溫度
 - 內置直流風扇強制風冷
 - 具有遙感功能
 - LED指示工作情况
 - 通過UL認證
 - 低成本，高信賴性
 - 100%滿載老化

- 輸入電壓範圍：90~132VAC/180~264VAC(開關置換)或254~370VDC
- 頻率範圍：47~63Hz
- 交流電流(Typ.): 10A/115VAC 6A/230VAC
- 浪湧電流(Typ.): 35A/115VAC 55A/230VAC
- 漏電流：<2.5mA/240VAC
- 尺寸：225*124*50mm(L*W*H)



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
58731	SE-450-3.3	MEAN WELL	450W 單組電源供應器	3.3V	75A	±3%
58733	SE-450-5	MEAN WELL	450W 單組電源供應器	5V	75A	±3%
58734	SE-450-12	MEAN WELL	450W 單組電源供應器	12V	37.5A	±1%
58706	SE-450-15	MEAN WELL	450W 單組電源供應器	15V	30A	±1%
58736	SE-450-24	MEAN WELL	450W 單組電源供應器	24V	18.8A	±1.5%
58737	SE-450-36	MEAN WELL	450W 單組電源供應器	36V	12.5A	±1%
58738	SE-450-48	MEAN WELL	450W 單組電源供應器	48V	9.4A	±1%

