



100W-375W PFC功能四組交換式電供器

詳細產品規格-請點擊www.100y.com.tw



- Features**
- Universal AC input / Full range
 - Built-in active PFC function, PF>0.95
 - Protections: Short circuit / Over load / Over voltage / Over temperature
 - With power good and fail signal output
 - Built-in remote sense function
 - LED indicator for power on
 - 100% full load burn-in test
 - Peak current capability



Part No.	Product No.	製造廠商	說明	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current
47099	QP-320D	MEAN WELL	320W PFC 四組交換式電供器	±3%	5V/2.5~20A	±3%	12V/0.0~10A	+10%,-6%	24V/0.2~5.0A	±10%	-12V/0.2~2A
39614	QP-320F	MEAN WELL	320W PFC 四組交換式電供器	±3%	5V/2.5~20A	±3%	15V/0.0~10A	+10%,-6%	24V/0.2~5.0A	±10%	-15V/0.2~1.6A



- 特性**
- 國際通用全範圍交流輸入
 - 內置主動式PFC功能, PF>0.95
 - 保護種類: 短路/過負載/過電壓/過溫度
 - 內置直流風扇強制風冷
 - CH3, CH4與其他輸出隔離且極性可以反轉
 - CH2, CH3, CH4無需最小負載
 - 所有輸出調整範圍是5~10%
 - 具有PG和PF信號輸出
 - 遙控開關
 - 開關工作頻率: 100KHz



Part No.	Product No.	製造廠商	說明	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current
21051	QP-375-24B	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±12V/0.0~4.0A	±1%	±12V/0.0~4.0A	±1%	5V/0.0~16A	±1%	24V/1.0~10A
21052	QP-375-24C	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±15V/0.0~4.0A	±1%	±15V/0.0~4.0A	±1%	5V/0.0~10A	±1%	24V/1.0~10A
21046	QP-375-5A	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±12V/0.0~3.0A	±1%	±12V/0.0~6.0A	±1%	12V/0.0~16A	±1%	5V/3.5~40A
21047	QP-375-5B	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±5V/0.0~3.0A	±1%	±12V/0.0~6.0A	±1%	12V/0.0~16A	±1%	5V/3.5~40A
21049	QP-375-5C	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±15V/0.0~4.0A	±1%	±15V/0.0~4.0A	±1%	12V/0.0~16A	±1%	5V/3.5~40A
17835	QP-375-5D	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±24V/0.0~3.0A	±1%	±12V/0.0~6.0A	±1%	12V/0.0~16A	±1%	5V/3.5~40A
21050	QP-375-5E	MEAN WELL	375W PFC 功能四組交換式電供器	±1%	±24V/0.0~3.0A	±1%	±24V/0.0~4.0A	±1%	12V/0.0~16A	±1%	5V/3.5~40A



- 特性**
- 保護種類: 短路/過負載/過電壓
 - 自然風冷
 - LED電源指示
 - 100%滿載老化
 - 全部使用105°C長壽命電解電容
 - 能承受300VAC浪湧輸入5秒
 - 工作溫度高達70°C
 - 承受5G振動測試
 - 高效率, 長壽命和高信賴度



Part No.	Product No.	製造廠商	說明	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current
62715	RT-125C	MEAN WELL	125W 三組輸出開關電源		5V · 15V · -15V		CH1:2-15A CH2:0.5~6A CH3:0.1~1A



- 特性**
- 國際通用交流輸入範圍(高達295VAC)
 - 保護種類: 短路/過負載/過電壓/過溫度
 - 輸出電壓和恆流值可調
 - 具有主動式PFC功能
 - IP66防護等級, 戶內, 戶外均可安裝
 - 自然風冷
 - 100%滿載老化測試
 - 高可靠性
 - 適用於LED照明和電子字幕屏等應用
 - 符合世界照明設備安全規範
 - 可應用於乾燥/潮濕/淋雨環境下



Part No.	Product No.	製造廠商	說明	Output Volt.	Tol.(±)	Output Current	重量
64777	CEN-100-20	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	20V	±10%	0~4.8A	0.60kg
64778	CEN-100-24	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	24V	±10%	0~4.0A	0.60kg
64779	CEN-100-30	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	30V	±10%	0~3.2A	0.60kg
64781	CEN-100-36	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	36V	±10%	0~2.65A	0.60kg
64783	CEN-100-42	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	42V	±10%	0~2.28A	0.60kg
64784	CEN-100-48	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	48V	±10%	0~2.0A	0.60kg
64785	CEN-100-54	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	54V	±10%	0~1.77A	0.60kg



- 特性**
- 國際通用交流輸入範圍(高達295VAC)
 - 保護種類: 短路/過負載/過電壓/過溫度
 - 輸出電壓和恆流值可調
 - 具有主動式PFC功能
 - IP66防護等級, 戶內, 戶外均可安裝
 - 自然風冷
 - 100%滿載老化測試
 - 高可靠性
 - 適用於LED照明和電子字幕屏等應用
 - 符合世界照明設備安全規範
 - 可應用於乾燥/潮濕/淋雨環境下



Part No.	Product No.	製造廠商	說明	Output Volt.	Tol.(±)	Output Current	重量
64745	CEN-60-12	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	12V	±10%	0~5.0A	0.56kg
64746	CEN-60-15	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	15V	±10%	0~4.0A	0.56kg
64747	CEN-60-20	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	20V	±10%	0~3.0A	0.56kg
64748	CEN-60-24	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	24V	±10%	0~2.5A	0.56kg
64749	CEN-60-30	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	30V	±10%	0~2.0A	0.56kg
64750	CEN-60-36	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	36V	±10%	0~1.7A	0.56kg
64751	CEN-60-42	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	42V	±10%	0~1.45A	0.56kg
64752	CEN-60-48	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	48V	±10%	0~1.3A	0.56kg
64753	CEN-60-54	MEAN WELL	MEAN WELL_PFC 功能單組交換式電供器(For LED 照明)	54V	±10%	0~1.15A	0.56kg

