



60-200W 參組交換式電源供應器

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)



- Universal AC input/Full range
- Low leakage current<180µA
- Protections: Short circuit / Overload / Over voltage
- UL60601-1 medical safety approved
- With power good and fail signal output (Optional)
- 100% full load burn-in test
- Fixed switching frequency at 45KHz



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
31732	MPT-120A	MEAN WELL	120W Triple Output Medical Type	-5V/0.0~1.0A	±5%	12V/0.4~5.8A	+8%,-6%	5V/2.0~12A	±2%
31734	MPT-120B	MEAN WELL	120W Triple Output Medical Type	-12V/0.0~1.0A	±5%	12V/0.4~5.3A	±6%	5V/2.0~12A	±2%
31735	MPT-120C	MEAN WELL	120W Triple Output Medical Type	-15V/0.0~1.0A	±5%	15V/0.4~4.4A	+6%,-7%	5V/2.0~11A	±2%
31736	MPT-120D	MEAN WELL	120W Triple Output Medical Type	12V/0.0~1.0A	±5%	24V/0.4~2.6A	+8%,-6%	5V/2.0~12A	±2%



- Universal AC input / Full range
- Low leakage current < 180µA
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Free air convection for 140W and forced air convection for 200W
- UL60601-1 medical safety approved
- With power good dan fail signal output
- Built-in remote ON-OFF control
- Built-in remote sense function
- Fixed switching frequency at 100KHz



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
31747	MPT-200A	MEAN WELL	200W Triple Output Medical Type	-5V/0.0~2.4A	±5%	12V/0.8~9.0A	±8%	5V/4.0~24A	±2%
31750	MPT-200B	MEAN WELL	200W Triple Output Medical Type	-12V/0.0~2.4A	±5%	12V/0.6~7.2A	±8%	5V/4.0~24A	±2%
31753	MPT-200C	MEAN WELL	200W Triple Output Medical Type	-15V/0.0~2.4A	±5%	15V/0.5~5.6A	±8%	5V/4.0~24A	±2%
31754	MPT-200D	MEAN WELL	200W Triple Output Medical Type	12V/0.0~2.4A	±5%	24V/0.3~3.6A	±8%	5V/4.0~24A	±2%



- 特性
- 國際通用全範圍交流輸入
  - 低漏電流≤0.3mA
  - 保護種類：短路/過負載/過電壓
  - 自然風冷
  - 100%滿載老化
  - 開關工作頻率：45KHz
- 輸入電壓範圍：90~264VAC或127~370VDC
  - 輸入頻率範圍：47~440Hz
  - 交流電流(Typ.)：1.6A/115VAC 1A/230VAC
  - 浪湧電流(Typ.)：冷啟動：20A/115VAC 40A/230VAC
  - 漏電流：<0.3mA/264VAC
  - 尺寸：127\*76\*42mm(L\*W\*H)



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
21143	MPT-65A	MEAN WELL	65W 三組輸出醫用型供應器	+5V/0.4~7.0A	±4%	+12V/0.2~3.2A	+10,-7%	-5V/0.0~0.7A	±5%
21144	MPT-65C	MEAN WELL	65W 三組輸出醫用型供應器	+5V/0.4~7.0A	±4%	+15V/0.2~2.6A	+10,-7%	-15V/0.0~0.7A	±5%



- 特性
- 國際通用全範圍交流輸入
  - 保護種類：短路/過負載/過電壓
  - 自然風冷
  - 100%滿載老化測試
- 輸入電壓範圍：85~264VAC或120~370VDC
  - 輸入頻率範圍：47~63Hz
  - 交流電流(Typ.)：1.5A/115VAC 0.9A/230VAC
  - 浪湧電流(Typ.)：冷啟動：45A
  - 漏電流：<2mA/240VAC
  - 尺寸：159\*97\*38mm(L\*W\*H)



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
30051	NET-75A	MEAN WELL	75W 參組交換式電源供應器	-5V/0.1~0.7A	±5%	12V/0.2~3.5A	±6%	5V/0.6~7.0A	±2%
30052	NET-75B	MEAN WELL	75W 參組交換式電源供應器	-12V/0.1~0.7A	±5%	12V/0.2~3.5A	±6%	5V/0.6~7.0A	±2%
30053	NET-75C	MEAN WELL	75W 參組交換式電源供應器	-15V/0.1~0.7A	±5%	15V/0.1~3.5A	±8%	5V/0.6~7.0A	±2%
30054	NET-75D	MEAN WELL	75W 參組交換式電源供應器	12V/0.1~1.5A	±6%	24V/0.1~2.0A	±8%	5V/0.6~6.0A	±2%



- 特性
- 國際通用全範圍交流輸入
  - 保護種類：短路/過負載/過電壓
  - 自然風冷
  - 100%滿載老化測試
  - 開關工作頻率：65KHz
- 輸入電壓範圍：90~264VAC或127~370VDC
  - 頻率範圍：47~63Hz
  - 交流電流(Typ.)：1.8A/115VAC 0.9A/230VAC
  - 浪湧電流(Typ.)：冷啟動：20A/115V 40A/230V
  - 漏電流：<1mA/240VAC
  - 尺寸：127\*76\*42mm(L\*W\*H)



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
29064	PT-6503	MEAN WELL	65W 三組輸出開關電源	3.3V/0.0~7.0A	±3%	5V/0.2~10A	+4%,-2%	12V/0.0~1.2A	±8%



- 特性
- 國際通用全範圍交流輸入
  - 漏電流<0.75mA
  - 保護種類：短路/過負載/過電壓
  - 自然風冷
  - 100%滿載老化測試
  - 開關工作頻率：65KHz
- 輸入電壓範圍：90~264VAC或127~370VDC
  - 頻率範圍：47~440Hz
  - 交流電流(Typ.)：1.5A/115VAC 0.9A/230VAC
  - 浪湧電流(Typ.)：冷啟動：20A/115V, 40A/230VAC
  - 漏電流：<0.75mA/240VAC



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
21015	PT-65A	MEAN WELL	65W 三組電源供應器	+5V/0.4~7A	±4%	+12V/0.2~3.2A	±7%	-5V/0.0~0.7A	±5%
16399	PT-65B	MEAN WELL	65W 參組交換式電源供應器	-12V/0.0~0.7A	±5%	+12V/0.2~3.2A	±7%	+5V/0.4~7.0A	±4%
15284	PT-65C	MEAN WELL	65W 參組交換式電源供應器	-15V/0.0~0.7A	±5%	+15V/0.2~2.6A	±7%	+5V/0.4~7A	±4%
21016	PT-65D	MEAN WELL	65W 三組電源供應器	+5V/0.5~5A	±4%	+12V/0.2~4A	±6%	+24V/0.2~1.3A	±6%

