



120-375W 四組交換式電源供應器

詳細產品規格-請點擊www.100y.com.tw



- 特性
- 交流輸入範圍通過開關置換
 - 保護種類：短路/過負載/過電壓
 - 100%滿載老化測試
 - 開關工作頻率：25KHz

- 輸入電壓範圍：88~132VAC/176~264VAC(開關選擇)或240~370VDC
- 頻率範圍：47~63Hz
- 交流電流(Typ.):2.8A/115VAC 1.6A/230VAC
- 浪湧電流(Typ.):冷啟動：35A
- 漏電流：<3.5mA/240VAC



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
11855	Q-120B	MEAN WELL	120W 四組輸出電源供應器	5VDC/2~12A	±2%	12VDC/0.5~5A	±6%	-12VDC/0.2~1A	±6%	-5VDC/0.2~1A	±6%
19475	Q-120C	MEAN WELL	120W 四組輸出電源供應器	5VDC/2~12A	±2%	15VDC/0.5~5A	+10,-5%	-5VDC/0.2~1A	±6%	-15VDC/0.2~1A	+10,-5%
12280	Q-120D	MEAN WELL	120W 四組輸出電源供應器	5VDC/2~12A	±2%	12VDC/0.2~5A	±6%	24VDC/0.2~2A	±6%	-12VDC/0.2~1A	±6%



- 特性
- 交流輸入範圍通過開關切換
 - 保護種類：短路/過負載/過電壓
 - 內置直流風扇強制風冷
 - 100%滿載老化測試
 - 開關工作頻率：75KHz
 - 低成本，高可靠



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
28059	Q-250B	MEAN WELL	250W 四組交換式電源供應器	5VDC/2.0~20A	±2%	12VDC/0.5~7A	+8%,-10%	-12VDC/0.5~1A	±10%	-5VDC/0~1A	±6%
30291	Q-250C	MEAN WELL	250W 四組交換式電源供應器	-5V/0.0~1.0A	±6%	-15V/0.5~1.0A	±10%	15V/0.5~5.0A	±10%	5V/2.0~20A	±2%
30292	Q-250D	MEAN WELL	250W 四組交換式電源供應器	-12V/0.0~1.0A	±6%	24V/0.5~5.0A	±8%	12V/0.5~6.0A	+6%,-10%	5V/2.0~15A	±2%
30293	Q-250F	MEAN WELL	250W 四組交換式電源供應器	-15V/0.0~1.0A	±6%	24V/0.5~5.0A	±8%	15V/0.5~5.0A	+6%,-10%	5V/2.0~15A	±2%



- 特性
- 保護種類：短路/過負載/過電壓
 - 自然風冷
 - LED電源指示燈
 - 100%滿載老化
 - 全部使用105°C長壽命電解電容
 - 能承受300VAC浪湧輸入5秒
 - 工作溫度高達70°C
 - 承受5G振動測試
 - 高效率，長壽命和高信賴性



Part No.	Product No.	製造廠商	說明	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)	Output Volt./Current	Tol.(±)
29868	RQ-125B	MEAN WELL	125W 四組交換式電源供應器	-12V/0.0~1.0A	±5%	-5V/0.1~1.0A	+6%,-10%	12V/0.5~4.5A	+8%,-3%	5V/2.0~12A	±2%
29883	RQ-125C	MEAN WELL	125W 四組交換式電源供應器	-15V/0.0~1.0A	±5%	-5V/0.1~1.0A	+6%,-10%	15V/0.5~4.0A	+8%,-3%	5V/2.0~12A	±2%
29885	RQ-125D	MEAN WELL	125W 四組交換式電源供應器	-12V/0.0~1.0A	±5%	24V/0.1~2.5A	±8%	12V/0.5~4.0A	+8%,-3%	5V/2.0~12A	±2%

300~1000W可並聯式交換式電源供應器

詳細產品規格-請點擊www.100y.com.tw



- Universal AC input / Full range
- AC input active surge current limiting
- Built-in active PFC function
- Protections: Short circuit / Overload / Over voltage / Over temperature
- Built-in constant current limiting circuit
- Current sharing up to 2 units or 2000W
- Built-in remote ON-OFF control
- Built-in remote sense function
- Built-in active current sharing and parallel function



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
30934	PSP-1000-5	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	5V	0~145A	±6%
30940	PSP-1000-12	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	12V	0~75.0A	±3%
30942	PSP-1000-13.5	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	13.5V	0~67.0A	±2%
30944	PSP-1000-15	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	15V	0~60.0A	±2%
30946	PSP-1000-24	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	24V	0~37.6A	±1%
30947	PSP-1000-27	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	27V	0~33.6A	±1%
30948	PSP-1000-48	MEAN WELL	MEAN WELL_1000W 可並聯式交換式電源供應器	48V	0~19.0A	±1%



- 特性
- 國際通用全範圍交流輸入
 - 內置主動式PFC功能
 - 保護種類：短路/過負載/過電壓/過溫度
 - 內置直流風扇強制風冷
 - DC OK信號輸出
 - 均流功能，最大2400W(3+1)
 - 遙控輸出開/關
 - 遙感功能
 - 開關工作頻率：PFC:88KHz PWM:100KHz



Part No.	Product No.	製造廠商	說明	Output Volt.	Output Current	Tol.(±)
30087	PSP-600-5	MEAN WELL	600W 可並聯式交換式電源供應器	5V	0~80.0A	±2%
30926	PSP-600-12	MEAN WELL	600W 可並聯式交換式電源供應器	12V	0~50.0A	±1%
30928	PSP-600-13.5	MEAN WELL	600W 可並聯式交換式電源供應器	13.5V	0~44.5A	±1%
30930	PSP-600-15	MEAN WELL	600W 可並聯式交換式電源供應器	15V	0~40.0A	±1%
30932	PSP-600-24	MEAN WELL	600W 可並聯式交換式電源供應器	24V	0~25.0A	±1%
30933	PSP-600-27	MEAN WELL	600W 可並聯式交換式電源供應器	27V	0~22.2A	±1%
27101	PSP-600-48	MEAN WELL	600W 可並聯式交換式電源供應器	48V	0~12.5A	±1%

