



直流轉直流-雙組電源轉換器

詳細產品規格-請點擊[www.100y.com.tw](http://www.100y.com.tw)



特性

- 2:1寬範圍輸入
- 4:1寬範圍輸入(可選)
- 1000VDC輸入/輸出隔離
- 3000VDC輸入/輸出隔離(可選)
- 內建EMI濾波電路
- 保護種類: 短路/過負載
- 自然冷卻
- 六面防護金屬外殼
- 100%滿載老化
- 低成本, 高可靠性
- 認證: FCC/CE



Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %
21276	DKE15A-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	9~18VDC	+1500mA	-5VDC	-1500mA	15W	81%
21280	DKE15B-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	18~36VDC	+1500mA	-5VDC	-1500mA	15W	83%
21273	DKE15C-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	36~72VDC	+1500mA	-5VDC	-1500mA	15W	79%
21277	DKE15A-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	9~18VDC	+625mA	-12VDC	-625mA	15W	82%
21281	DKE15B-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	18~36VDC	+625mA	-12VDC	-625mA	15W	83%
21274	DKE15C-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	36~72VDC	+625mA	-12VDC	-625mA	15W	82%
21278	DKE15A-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	9~18VDC	+500mA	-15VDC	-500mA	15W	82%
21282	DKE15B-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	18~36VDC	+500mA	-15VDC	-500mA	15W	83%
8391	DKE15C-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	36~72VDC	+500mA	-15VDC	-500mA	15W	82%
21279	DKE15A-24	MEAN WELL	直流轉直流-雙組-電源轉換器	+24VDC	9~18VDC	+313mA	-24VDC	-313mA	15W	82%
21283	DKE15B-24	MEAN WELL	直流轉直流-雙組-電源轉換器	+24VDC	18~36VDC	+313mA	-24VDC	-313mA	15W	84%
21275	DKE15C-24	MEAN WELL	直流轉直流-雙組-電源轉換器	+24VDC	36~72VDC	+313mA	-24VDC	-313mA	15W	85%




特性

- 2:1寬範圍輸入
- 4:1寬範圍輸入(可選)
- 1000VDC輸入/輸出隔離
- 3000VDC輸入/輸出隔離(可選)
- 內建EMI濾波電路
- 保護種類: 短路/過負載
- 自然冷卻
- 六面防護金屬外殼
- 100%滿載老化
- 低成本, 高可靠性
- 認證: FCC/CE



Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %
21232	DLW05A-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	9~18VDC	+500mA	-5VDC	-500mA	5W	75%
21234	DLW05B-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	18~36VDC	+500mA	-5VDC	-500mA	5W	77%
21236	DLW05C-05	MEAN WELL	直流轉直流-雙組-電源轉換器	+5VDC	36~72VDC	+500mA	-5VDC	-500mA	5W	77%
21233	DLW05A-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	9~18VDC	+208mA	-12VDC	-208mA	5W	80%
21235	DLW05B-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	18~36VDC	+208mA	-12VDC	-208mA	5W	82%
21237	DLW05C-12	MEAN WELL	直流轉直流-雙組-電源轉換器	+12VDC	36~72VDC	+208mA	-12VDC	-208mA	5W	83%
8413	DLW05A-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	9~18VDC	+167mA	-15VDC	-167mA	5W	81%
11615	DLW05B-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	18~36VDC	+167mA	-15VDC	-167mA	5W	83%
21238	DLW05C-15	MEAN WELL	直流轉直流-雙組-電源轉換器	+15VDC	36~72VDC	+167mA	-15VDC	-167mA	5W	85%



特性

- 4:1寬範圍直流輸入
- 保護種類: 短路/過負載/過電壓/過溫度
- 1500VDC輸入/輸出隔離
- 內置EMI濾波電路
- 自然風冷
- 輸出電壓調節功能
- 內置遙控開/關
- 100%滿載老化測試
- 低成本, 高可靠



Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %	重量
55371	NSD15-12D5	MEAN WELL	15W DC-DC 雙組電源轉換器	5V	12VDC	1.5A	-5V	1.5A	15W	76%	26.2g



- 效率高達81%
- 3000VDC隔離
- MTBF>2,000,000 Hours
- 低消耗
- 5, 12, 24VDC輸入
- 3.3, 5, 9, 12, 15, ±5, ±9, ±12, ±15VDC輸出
- 溫度範圍: -40°C to +85°C
- UL 94V-0包裝材料
- 工業標準引腳

Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %
21569	MAU218	MINIMAX	直流轉直流-雙組-電源轉換器	+12V	10.8~13.2V	+42mA	-12V	-42mA	1W	81%



- Input voltage range: ±10%
- Input filter: Capacitor
- Output voltage accuracy: ±5%
- Line voltage regulation: 1.2% TYP / 1% Of Vin
- 5V Output Types: 15% Max
- 9V, 12V And 15V Output Types: 10% Max

Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %	重量
50753	MSV-0509D	CTC	直流轉直流-雙組-電源轉換器	9V	5V	55mA	-9V	-55mA	1W	75%	2.2g



- RoHS compliant
- 效率高達79%
- Power density up to 0.85W/cm<sup>3</sup>
- Wide temperature performance at full 1 Watt load, -40°C to 85°C
- Single or dual output
- UL94V-0包裝材料
- 額定性能運行時無需散熱片
- 3kV輸入/輸出隔離



Part No.	Product No.	製造廠商	說明	DCVout	DCVin	Current	DCVout	Current	Watts	Efficiency %
68504	NMV0512SC	MuRata	MuRata Ps 1W 雙路輸出直流/直流轉換器	-12VDC	-5VDC	-42mA	+12VDC	+42mA	1W	78%
68506	NMV0515SC	MuRata	MuRata Ps 1W 雙路輸出直流/直流轉換器	-15VDC	5VDC	-33mA	+15VDC	+33mA	1W	79%

