

RELAYS & SOLENIIDS


PartNo	ProductNo.	Manuf.	Description	ContactRating	ContactArrangement	CoilVoltage	RecognizedSafety	OutlineLxWxH
14874	G2R-1-E	OMRON	"OMRON" POWER RELAY	16A250VDC/16A 30VDC	SPDT	12VDC	CSA, VDE	28.6*12.6*24.9



E53-R 輸出模組額定E5AK/E5EK型用
E53-R型繼電器AC250V 5A (阻抗負載)ON-OFF
COIL:24VDC
繼電器輸出壽命電氣的-1萬次以上



PartNo	ProductNo.	Manuf.	Description	ContactRating	Type	CoilVoltage	RecognizedSafety	OutlineLxWxH
11629	E-53R	OMRON	For E5系列溫控器維修用Relay	250VAC/5A	E-53	24VDC	CSA	20*14.5*9.5mm




Suitableforhandlinglowsignalsincomputer peripherals,telecommunicationsandsecurity equipment. Capableofswitchingloadsupto2A. ConformstoFCCpart681500Vsurge withstand. Reliablebifurcatedcrossbarcontacts. Fully-sealedconstruction.

PartNo	ProductNo.	Description	ContactRating	Type	ContactArrangement	CoilVoltage	RecognizedSafety	OutlineLxWxH
17281	G5V-2-DC24V	General Usage 2A Relay	0.6A/125VAC,0.6A/110VDC,2.0A/30VDC	G5V-2	DPDT	3~48V,3~24V	UL/CSA	10.1*20.5*11.5
18174	G5V-2-H1-5V	High-sensitivityRelay	0.5A/125V,1.0A/24VDC	G5V-2-H1	DPDT	5V	UL/CSA	10.1*20.5*11.5



Highsensitivityandcanbedrivenbydigital circuits Unitscanbemountedsidebysideduetolow magneticleakage High reliability Surge withstandvoltage-meetsFCCPart68 regulation Singleorduallatchingcoiltypesavailable

Specialmodelsavailableforultrasoniccleaning andlowthermoelectromotiveforce
Dimensions
Height .3200Inches
Length .7900Inches
Width .3900Inches
Approvals
ULApproval
CSAApproval




PartNo	ProductNo.	Description	ContactRating	Type	ContactArrangement	CoilVoltage	RecognizedSafety	OutlineLxWxH
16195	G6A-274P-ST-US-12VDC	PCB繼電器	0.6A/125VAC,2A/30VDC	G6A-274P-ST-US	2C	DC12V	UL,CSA	20.2*10.1*8.4
12350	G6A-274P-ST-US-24VDC	PCB繼電器	0.6A/125VAC,2A/30VDC	G6A-274P-ST-US	2C	DC24V	UL,CSA	20.2*10.1*8.4
16194	G6A-274P-ST-US-5VDC	PCB繼電器	0.6A/125VAC,2A/30VDC	G6A-274P-ST-US	2C	DC5V	UL,CSA	20.2*10.1*8.4




Highsensitivityandcanbedrivenbydigitalcircuits High reliability Surge withstandvoltage-meetsFCCPart68 regulation Unitscanbemountedsidebysideduetolow magneticleakage Specialmodelsavailableforultrasoniccleaning andlowthermoelectromotiveforce


Singleorduallatchingcoiltypesavailable
Dimensions
Height .3200Inches
Length .7900Inches
Width .3900Inches
Approvals
ULApproval
CSAApproval



PartNo	ProductNo.	Description	ContactRating	Type	ContactArrangement	CoilVoltage	RecognizedSafety	OutlineLxWxH
16888	G6AK-234P-DC12V	PCB繼電器	2A	G6AK-234P	DPDT	DC12V	UL,CSA	20.2*10.1*8.4




Lowpowerconsumption:200mW. Uniquemovinglooparmaturereducesrelay size,magneticinterference,andcontact bounce-time. Single-anddouble-windinglatchingtypes alsoavailable.



PartNo	ProductNo.	Description	ContactRating	Type	ContactArrangement	CoilVoltage	RecognizedSafety	OutlineLxWxH
17980	G6B-2214P-US-DC24V	Straight PCB Relay	8A/250Vac,5A/30Vdc	G6B-2214P-US	DPST-NO	DC24V	CSA,RL,	20*10*10
17200	G6C-2117P-US-12VDC	PCB Relay	8A/250Vac,8A/30Vdc	G6C-2117P-US	SPST-NO+SPST-NC	DC12V	CSA	20.07*14.99*9.91



Impulsethstandvoltageof10,000Vbetween inputandoutput(coilandcontact) Creepage-distanceof10mm(0.39in)minimum betweencoilandcontactmeetsVDE/C250 Dielectricstrengthof4,000VACminimum conformstoUL,CSAandIECClassII International2.5mm(0.10in)terminalpitch Lowpowerconsumption(0.8W)



PartNo	ProductNo.	Description	ContactRating	Type	ContactArrangement	CoilVoltage	RecognizedSafety
23811	G4W-2214P-US-HP	Power Relay	1/4HP,125VAC	G4W-2214P-US	DPST-NO	DC24V	6~120VDC

