

RELAYS & SOLENIIDS


PartNo.	ProductNo.	Manuf.	Description	Coil rating	Contactrating	Contactform
4869	MK3P-I-110VAC	OMRON	11 Pins Coil繼電器	250Vac,28Vdc/10A	110Vac	3PDT
12473	MK3P-I-12VDC	OMRON	11 Pins Coil繼電器	250Vac,28Vdc/10A	12Vdc	3PDT
4870	MK3P-I-220VAC	OMRON	11 Pins Coil繼電器	250Vac,28Vdc/10A	220Vac	3PDT
12786	MK3P-I-24VAC	OMRON	11 Pins Coil繼電器	250Vac,28Vdc/10A	24Vdc	3PDT
4868	MK3P-I-24VDC	OMRON	11 Pins Coil繼電器	250Vac,28Vdc/10A	24Vdc	3PDT

TOWARD-MK28角圓形繼電器 TOWARD-MK28PlugRelays

詳細產品規格--請點擊www.100y.com.tw




Features
 Highswitchingcapacity.
 Ruggedconstructionforthoughapplications.
 Within LEDavailable, Testingbutton.




PartNo.	ProductNo.	Manuf.	Description	Coil rating	Contactrating	Contactform
15905	BMK2-110A	TOWARD	8角圓形Coil 繼電器	110Vac	5A220Vac/28Vdc	2From C
15903	BMK2-12D	TOWARD	8角圓形Coil 繼電器	12Vac	5A220Vac/28Vdc	2From C
15906	BMK2-200/240A	TOWARD	8角圓形Coil 繼電器	220Vac	5A220Vac/28Vdc	2From C
15907	BMK2-240A	TOWARD	8角圓形Coil 繼電器	240Vac	10A 250Vac/28Vdc	2From C
15904	BMK2-24D	TOWARD	8角圓形Coil 繼電器	24Vac	5A220Vac/28Vdc	2From C

繼電器角座 8-Pin/11-Pin 圓形繼電器底座 8-Pin and 11-Pin Track Mounted Sockets


詳細產品規格--請點擊www.100y.com.tw



Eachunitprovidesfivefield-selectabletimerangesusingthefrontpaneltimerange selector
 ON-delayorSignalOFF-delayfromclutchinputareavailable
 Neontimingindicatorandmovingpointershowstatus
 Panelmountingadapters,sockets,protectivecoverandotheraccessoriesmaybe orderedseparately



PartNo.	ProductNo.	Manuf.	Description	Pins	重量	L*W*H(mm)
11970	P2CF-11	OMRON	11 Pins 圓繼電器腳座	11P	70g	70*50*25




PartNo.	ProductNo.	Manuf.	Description	Pins	重量	L*W*H(mm)
4871	PF083A-L	OMRON	8 Pins 圓繼電器腳座	8 P	34g	52*41*21
4339	PF113A-L	OMRON	11 Pins 圓繼電器腳座	11P	47g	52*42.8*31



Features:
 Fieldselectabletimerangesfrom0.05secondsto300hours.
 Choose6-or2-functionmodelstofitmostapplications
 WiderangeACsupplyvoltagemodels(100-240VAC)fitmost applicationsandreducesparepartsinventories
 Short(80mm)panelmountingdepthwithsocketallowsformore space-efficientcontrolpaneldesign

Specifications:
 Controloutputtype:DPDTrelay
 Supplyvoltage:100-240VAC/24VACor12VDCor24VDC
 Maximumload:5A@250VAC
 Timingfunctionsfor11-pinround:ON-delay,Repeatcycle,signal ON/OFFdelay,signalOFFdelay,interval
 TimingFunctionsfor8-pinround:ON-delay,interval



PartNo	ProductNo.	Manuf.	Description	Pins	重量	L*W*H(mm)
11040	P3G-08	OMRON	圓繼電器腳座 Socket Back Mounting, for use with Y92F-30 Mounting Adapter Bottom Screw Terminals	8P	40g	48*40*20

方形繼電器底座 General Track Mounted Sockets

詳細產品規格--請點擊www.100y.com.tw

詳細產品規格--請點擊www.100y.com.tw

