


SEMICONDUCTORS-DISCRETES

PartNo.	ProductNo.	Manuf.	Description	IF(A)	Vrrm/V	Pins/Package
8130	BR108	LITE-ON	插板式橋式整流器	10A	800V	BR-10
27493	KBPC206		橋式整流器	2A	600V	RS-21
8491	KBPC1504W	LITE-ON	插板式橋式整流器	15A	400V	KBPC-W
4012	KBPC2506W	LITE-ON	插板式橋式整流器	25A	600V	KBPC-W
8050	KBPC2508W	LITE-ON	插板式橋式整流器	25A	800V	KBPC-W
7743	KBPC3510T	LITE-ON	焊接式橋式整流器	35A	1000V	KBPC
8132	KBPC806	LITE-ON	插板式橋式整流器	8A	600V	PBPC-8(BR-10)
8129	PBPC1006	LITE-ON	焊接式橋式整流器	10A	800V	PBPC-8
7742	PBPC605	LITE-ON	插板式橋式整流器	6A	600V	PBPC-6


三相整流器

Three Phase Rectifiers

詳細產品規格--請點擊www.100y.com.tw



30G6P41



20L6P45



DF60AA120

TjMax=150
IsolatedMountingBase
Highreliabilitybyuniqueglass
passivation(Applications)

PartNo.	ProductNo.	Manuf.	Description	IF(A)	Vrrm/V	Pins/Package
16474	20L6P45	TOSHIBA	三相整流器	20A	800V	12-46A1A
16507	30G6P41	TOSHIBA	三相整流器	30A	1000V	
16644	DF60AA120	TTICL	DIODE 模組	60A	1200V	

瞬間電壓抑制二極管(TVS)

1.5KE-瞬間電壓抑制二極管

1.5KE-TVS

詳細產品規格--請點擊www.100y.com.tw




DO-201

PartNo.	ProductNo.	Description	Power	Stand-offVrrm	Vbrmin	Vbrmax	單向/雙向	Package
22120	1.5KE16CA	瞬變電壓抑制二極管	1500W	13.6V	15.2V	16.8V	雙向	DO-201
22123	1.5KE18CA	瞬變電壓抑制二極管	1500W	15.3V	17.1V	18.9V	雙向	DO-201
22130	1.5KE250CA	瞬變電壓抑制二極管	1500W	214V	237V	263V	雙向	DO-201
19763	1.5KE300A	瞬變電壓抑制二極管	1500W	256V	285V	315V	單向	DO-201
22112	1.5KE30CA	瞬變電壓抑制二極管	1500W	25.6V	28.5V	31.5V	雙向	DO-201
22128	1.5KE33CA	瞬變電壓抑制二極管	1500W	28.2V	31.4V	34.7V	雙向	DO-201
22132	1.5KE350CA	瞬變電壓抑制二極管	1500W	300V	332V	368V	雙向	DO-201
22127	1.5KE43CA	瞬變電壓抑制二極管	1500W	36.8V	40.9V	45.2V	雙向	DO-201
22129	1.5KE51CA	瞬變電壓抑制二極管	1500W	43.6V	48.5V	53.6V	雙向	DO-201
22131	1.5KE6.8CA	瞬變電壓抑制二極管	1500W	5.8V	6.45V	7.14V	雙向	DO-201
27870	1.5KE68CA	瞬變電壓抑制二極管	1500W	58.10V	64.60V	71.40V	雙向	DO-201

5KP-瞬間電壓抑制二極管

5KP-TVS

詳細產品規格--請點擊www.100y.com.tw



5KPSERIESEVICESPECIFICATIONS
BuiltWithSussexGlassPassivatedDies
AvailableasUni-andBi-Directional
EachDeviceIndividuallyInspected
MoldedEpoxyPackage
OperatingTemperature:-55to175C


StorageTemperature:-55to175C
MarkedWithSussexLogo,PartNumber,and
CathodeBandonUnipolarTypes
PlatedLeads,SolderablePerMIL-STD-750
Method2026
UnderwriterLaboratoriesApproved

PartNo.	ProductNo.	Description	Power	Stand-offVrrm	Vbrmin	Vbrmax	單向/雙向	Package
15964	5KP30A	TransientVoltage Suppressors	5000W(min)	30V	6.4V	7.3V	單向	R-6(CASE12)

BWZ-瞬間電壓抑制二極管

BWZ-TVS

詳細產品規格--請點擊www.100y.com.tw



Features
PlasticpackagehasUnderwritersLaboratory
FlammabilityClassification94V-0
Glasspassivatedjunction
UniandBidirectionalTypesAvailable
ExcellentclampingCapability

Lowincrementalsurgesresistance
Fastresponsetime:theoretically(withnoparisitic
inductance)lessthan1.0psfrom0VtoV(BR)for
unidirectionaland5.0nsforbi-directional
types
Hightemperature soldering guaranteed:265 /10
seconds,0.375"(9.5mm)leadlength,5lbs.(2.3kg)tension

PartNo.	ProductNo.	Description	Power	Stand-offVrrm	Vbrmin	單向/雙向	Package
16669	BZW06-28	TransientVoltage Suppressors	600W	28.2V	31.4V/1mA	單向	DO-15

