



LOGIC IC



| Part No. | ProductNo. | Manuf. | Description | Pins/Package | Vcc | Icc(mA) | OperatingTemp. |
|----------|------------|------------|---|------------------|-----------|---------|----------------|
| 658 | 74HC04 | HITACHI | Hex Inverter | 14P/DIP | 2-6V | 20uA | -40~+125 |
| 13892 | 74HC04D | HITACHI | Hex Inverter | 14P-SOIC | 2-6V | 20uA | -40~+85C |
| 19219 | 74HC04D | PHILIPS | Hex Inverter | 14P-SOIC | 2-6V | 20uA | -40~+125C |
| 19221 | 74HC08N | PHILIPS | Quad 2-Input AND Gate | 14P-DIP | 2-6V | 20uA | -40~+125C |
| 20586 | 74HC123D | PHILIPS | Dual retriggerable monostable multivibrator with reset | 16P/SO(SOT109-1) | 5V | | |
| 679 | 74HC138 | PHILIPS | 3-to-8 line Decoder | 16P/DIP | 2-6V | ±20mA | -40~85C |
| 19253 | 74HC138D | PHILIPS | | | | | |
| 6394 | 74HC14D | PHILIPS | HEX SCHMITT-TRIGGER INVERTERS | 14P/SOIC | 2-6V | 20mA | -40~85C |
| 22246 | 74HC14N | PHILIPS | 74HC14N.pdf | 14P/DIP | 2-6V | 50mA | -40~125 C |
| 22247 | 74HC151D | PHILIPS | 8-input multiplexer | 16P/SOIC | 2-6V | | 0~70C |
| 22250 | 74HC157N | GS Battery | Quad 2-Input Multiplexer | 16P/PDIP | -0.5~7.0V | 50mA | -40~85 C |
| 4882 | 74HC165 | Fairchild | Parallel-in/Serial-out 8-Bit Shift Register | 16P/DIP | 5V | ±50mA | -40~85C |
| 1035 | 74HC174D | PHILIPS | Hex D-Type Flip-Flops with Clear | 16P/SOIC | 2-6V | 160mA | -40~85C |
| 19263 | 74HC191D | PHILIPS | | | | | |
| 22258 | 74HC192B1R | ST(SGS) | SYNCHRONOUS UP/DOWN DECADE COUNTER | 16P/DIP | -0.5~7V | 80mA | |
| 696 | 74HC221 | ST(SGS) | Dual Non-Retriggerable Monostable Multivibrator | 16P/DIP | 2-6V | ±50mA | -40~85C |
| 697 | 74HC238B1R | ST(SGS) | 3-TO-8 Line Decoder / Demultiplexer | 16P/DIP | 2-6V | ±50mA | -55~125C |
| 16895 | 74HC243D | ST(SGS) | Quad bus transceiver; 3-state | SOIC-14P | 0.5~7V | ±50mA | -40~85C |
| 19224 | 74HC244D | PHILIPS | Octal 3-STATE Buffer | 20P/SOIC | 2-6V | ±70mA | -40~85C |
| 19223 | 74HC244N | PHILIPS | Octal 3-STATE Buffer | 20P/DIP | 2-6V | ±70mA | -40~85C |
| 19226 | 74HC245D | PHILIPS | Octal bus transceiver; 3-state | 20P/SOIC(300mil) | 2-6V | 40mA | -40~85C |
| 19225 | 74HC245N | PHILIPS | | DIP | | | |
| 22268 | 74HC259N | Fairchild | 8-Bit Addressable Latch/3-to-8 Line Decoder | 16P/PDIP | -0.5~7.0V | 50mA | -65~150C |
| 22270 | 74HC273D-T | PHILIPS | Octal D-type flip-flop with reset; positive-edge trigger | 20P | 2-6V | | -40~85C |
| 22275 | 74HC30D | PHILIPS | 8-input NAND gate | 14P/DIP | 5V | | -40~125C |
| 11327 | 74HC32D | PHILIPS | QUADRUPLE 2-INPUT POSITIVE-OR GATES | 14P/SOIC | 2-6V | 20mA | -40~85C |
| 19229 | 74HC32D | Fairchild | QUADRUPLE 2-INPUT POSITIVE-OR GATES | 14P/SOIC | 2-6V | 20mA | -40~85C |
| 22278 | 74HC366N | MATSUSHITA | Hex 3-State Inverting Buffer with Common Enables | 16P/DIP | -0.5~7V | 75mA | -65~150C |
| 11302 | 74HC373D | PHILIPS | 3-STATE Octal D-Type Latch | 20P/SOIC(300mil) | 2-6V | 80mA | -40~85C |
| 19234 | 74HC374D | PHILIPS | 3-STATE Octal D-Type Flip-Flop | 20P-SOIC | 2-6V | | -40~85C |
| 22285 | 74HC377E | HARRIS | High-Speed CMOS Logic Octal D-Type Flip-Flop With Data Enable | 20P/PDIP | -0.5~7V | 50mA | -55~125 |
| 19236 | 74HC390N | PHILIPS | | DIP | | | |
| 716 | 74HC393D | PHILIPS | Dual 4-bit binary counter | 14P/DIP | 2-6V | ±50mA | -40~85C |
| 22287 | 74HC4002N | PHILIPS | Dual 4-input NOR gate | 14P/DIP | 2-6V | | -40~85C |
| 728 | 74HC4015 | PHILIPS | Triple 3-input positive-and Gate | 16P/DIP | 2-6V | ±50mA | -40~85C |
| 27933 | 74HC4051D | PHILIPS | High Speed CMOS Logic Analog Multiplexers/Demultiplexers | 16P/SOIC | 5V | 50mA | -55~125 C |
| 735 | 74HC4053 | PHILIPS | Triple 2-Channel Analog Multiplexer | 16P/DIP | 2-6V | ±50mA | -55~125C |
| 23874 | 74HC4060D | PHILIPS | 14 Stage Binary Counter | 16P/SOIC | 2-6V | | -40~85C |
| 22305 | 74HC4066PW | PHILIPS | Quad bilateral switches | 14P/SSOP | 4.5~9V | 50mA | -40~125C |
| 22306 | 74HC4075N | PHILIPS | Triple 3-input OR gate | 14P | 2-6V | | -40~125C |
| 720 | 74HC541 | PHILIPS | Octal Buffers and Line Drivers with 3-state outputs | 20P/DIP | 2-6V | ±70mA | -40~85C |
| 22309 | 74HC563BIN | ST(SGS) | HC563 Inverting -HC573 Non Inverting Octal D-type Latch With 3 State Output | 20P/DIP | 2-6V | 4mA | -40~85 |
| 22195 | 74HC573D | PHILIPS | Octal D-type transparent latch; 3-state | 20P/SOIC | | | |
| 19239 | 74HC573N | PHILIPS | Octal D-type transparent latch; 3-state | 20P/DIP | 2-6V | ±35mA | -40~+85C |
| 23907 | 74HC595D | Fairchild | 8-bit serial-in/serial or parallel-out shift register with output latches | 16P/SOIC | 5V | | -40~+85C |
| 22314 | 74HC595MX | ST(SGS) | 8 Bit Shift Register With Output Latches (3 State) | 16P/DIP | 2V~6V | 4mA | -65~150 |
| 4873 | 74HC688 | PHILIPS | 8-bit Mag. Comparator | 20P/DIP | 2-6V | | -40~85C |
| 19242 | 74HC688D | PHILIPS | | | | | |
| 19243 | 74HC74D | PHILIPS | Dual D Flip Flop with Preset and Clear | SOT-108(SO-14) | 2-6V | ±60 mA | -40~125C |
| 22199 | 74HC74N | PHILIPS | Dual D Flip Flop with Preset and Clear | 14P/DIP | 2-6V | ±60 mA | -40~125C |
| 22318 | 74HC75N | PHILIPS | Quad bistable transparent latch | 16P | 2-6V | | -40~85C |
| 4092 | 74HC93 | HARRIS | 4-Bit Binary Counter | 14P/DIP | 2-6V | ±50mA | -55~125C |
| 10090 | 74HC93D | PHILIPS | High Speed CMOS Logic 4-Bit Binary Ripple Counter | 14P/SOIC | 2-6V | 80mA | -40~85C |
| 1013 | 74HCT00D | N.S | Quad 2 Input NAND Gate | 14P/SOIC | 4.5~5.5V | 40mA | -40~85C |
| 10616 | 74HCT04DT | PHILIPS | HEX INVERTERS | 14P/SOIC | 4.5~5.5V | 20mA | -40~85C |
| 1019 | 74HCT125D | PHILIPS | Quadruple Bus Buffer Gates With 3-state Outputs | 14P/SOIC | 4.5~5.5V | 2.9mA | -40~85C |
| 6396 | 74HCT175D | PHILIPS | Quad D-type flip-flop with reset; positive-edge trigger | 16P/SOIC | 2-6V | 160mA | -40~85C |

