

SOLDERING & DESOLDERING



120V, 60Hz, 每支烙鐵70W功率
 固態控制, 溫度調整, 自400 至800 (205 至427)
 溫度飄移為 ± (±)
 自烙鐵頭至接地點間之漏電壓不逾mv
 零電壓切換
 防靜電結構
 烙鐵輕便, 操作容易
 圓筒狀陶瓷導熱管, 加熱迅速, 不易破損斷線, 最具經濟性

Angle Face Tips

Part #	Graphic	Description	a Width	b Length
LT373		Small Angle Face	.09" (2.3 mm)	.59" (15 mm)
LT398		Medium Angle Face	.12" (3.0 mm)	.59" (15 mm)
LT399		Large Angle Face	.16" (4.0 mm)	.59" (15 mm)
LT445		SMD Angle Face	.03" (0.8mm)	.48" (12.2mm)
LT387		Standard Angle Face	.06" (1.5mm)	.48" (12.2mm)
LT393		Extra-Long Angle Face	.06" (1.5mm)	.94" (23.9mm)
LT430		Mid-Length Angle Face	.06" (1.5mm)	.74" (18.9mm)

Needle Tips

Part #	Graphic	Description	a Width	b Length
LT374		Standard Probe	.03" (0.8mm)	.48" (12.2mm)
LT380		Short Cone	.02" (0.5mm)	.32" (8.1mm)
LT381		Standard Cone	.02" (0.5mm)	.47" (11.9mm)
LT382		Long Cone	.02" (0.5mm)	.62" (15.7mm)
LT383		Thin Mid-Length Needle Point	.02" (0.5mm)	.72" (18.2mm)
LT429		Mid-Length Needle Point	.02" (0.5mm)	.74" (18.9mm)
LT439		Thin SMD Probe	.03" (0.8mm)	.50" (12.7mm)
LT446		SMD Probe	.03" (0.8mm)	.48" (12.2mm)
LT442		SMD Mid-Length Probe	.04" (1.0mm)	.74" (18.9mm)
LT603		SMD Mid-Length Needle	.02" (0.5mm)	.69" (17.5mm)

EDSYN® Spade Tips

Part #	Graphic	Description	a	b
LT371		Fine Spade	.09" (0.8 mm)	.55" (14.0 mm)
LT375		Standard Spade	.06" (1.5mm)	.48" (12.2mm)
LT376		Short Stubby Spade	.12" (3.0mm)	.48" (12.2mm)
LT394		Extra-Long Spade	.07" (1.8mm)	.93" (23.6mm)
LT395		Mid-Length Stubby Spade	.09" (2.3mm)	.74" (18.9mm)
LT425		Extra-Long Fine Spade	.05" (1.3mm)	.93" (23.6mm)
LT431		Mid-Length Spade	.07" (1.8mm)	.74" (18.9mm)
LT424		Mid-Length Angle Spade	.06" (1.5mm)	.74" (18.9mm)
LT444		SMD Mid-Length Fine Spade	.04" (1.0mm)	.78" (19.8mm)

PartNo.	ProductNo.	Manuf.	Description	適用焊槍機型	長度 (mm)	尖端尺寸 (mm)	防靜電 Y/N
13390	LT-376	EDSYN	日製烙鐵頭	951SX	12.2mm	3.0mm	YES
27104	LT-382	EDSYN	日製烙鐵頭	951SX	15.7mm	0.5mm	YES
12728	LT-395	EDSYN	日製烙鐵頭	951SX	18.9mm	2.3mm	
12727	LT-398	EDSYN	日製烙鐵頭	951SX	15mm	3.0mm	YES
14372	LT-429	EDSYN	日製烙鐵頭	951SX, CL-1180, CL-1080	18.9mm	0.5mm	
18762	LT-446	EDSYN	日製烙鐵頭SMD Probe	951SX	12.2mm	0.8mm	YES

EDSYN-981數位式溫控烙鐵台+配件 EDSYN-981 HeatSolderingIron+ Accessories

詳細產品規格--請點擊 www.100y.com.tw



PartNo.	ProductNo.	Manuf.	Description	適用焊槍機型	長度 (mm)	尖端尺寸 (mm)	形狀
14035	LT-375	EDSYN	烙鐵頭	951SX	12.2mm	1.5mm	Standard Spade

其它品牌 - - 烙鐵+配件 手握式木柄烙鐵 + 烙鐵頭 SolderingIron+AvailableTipShape

詳細產品規格--請點擊 www.100y.com.tw



Keep iron dry..Moisture will damage the heating element.
 Keep tip fully inserted and tight in iron when soldering.
 Do not operate iron without tip, or with a short tip, or with a tip pulled out from the element as iron will then overheat and shorten the life.
 Keep tip in need at all times.
 Do not operate iron continuously without using it. LINGCHUN IRONS are made to solder with.
 Do not strike iron unnecessarily. LINGCHUN IRONS are the most rugged. But longer life will result if striking or jarring iron is eliminated.

