


# INDUCTORS & SUPPRESSORS & FILTERS





特性：  
 電感範圍：1.0uH到10000uH之間。  
 額定電流基於電流強度約為8.0A/mm<sup>2</sup>。  
 額定頻率：“-26”：50Hz~100KHz；“-52”：10KHz~500KHz。  
 工作溫度：-55°C到125°C。  
 測試儀器：電感值：使用LCR儀器在1KHz的頻率下測量  
 直流電阻：毫安表(Milli-ohmmeter)

| PartNo. | ProductNo.           | Description         | 完成品直徑*厚D  | I.d.c.max.(A) | 電感值@1KHz(uH) | d.c.Res.(Mil.) | 誤差值(%) |
|---------|----------------------|---------------------|-----------|---------------|--------------|----------------|--------|
| 27910   | LFD648075-14TX2-3LL  |                     |           |               | 100uH        | 1500           |        |
| 27744   | LFD707010-11U-1.5A   |                     |           | 1.5A          | 11uH         | 18m            |        |
| 3915    | TC-100M-2A-3026      | 中空圓環繞線式電感           | 10.5*5.5  | 2             | 10           | 13             | ±0%    |
| 2688    | TC-101M-2A-5026      | 中空圓環繞線式電感           | 15.0*8.0  | 2.0           | 100.0        | 5.3            | ±0%    |
| 3854    | TC-101M-5A-10626     | 中空圓環繞線式電感           | 32.0*15.0 | 5             | 100          | 31.6           | ±0%    |
| 3910    | TC-120M-1A-3026      | 中空圓環繞線式電感           | 9.5*5.0   | 1             | 12           | 27             | ±0%    |
| 9965    | TC-131M-1A-6026      | 中空圓環繞線式電感           | 17*8      | 1A            | 130          | 114            | ±0%    |
| 3909    | TC-150M-0.5A-2026    | 中空圓環繞線式電感           | 6.0*3.0   | 0.5           | 15           | 58             | ±0%    |
| 3902    | TC-150M-2A-4426      | 中空圓環繞線式電感           | 13*6      | 2             | 15           | 20.5           | ±0%    |
| 9963    | TC-151M-1A-6826      | 中空圓環繞線式電感           | 21*8      | 1A            | 150          | 124            | ±0%    |
| 3912    | TC-200M-0.2A-2026    | 中空圓環繞線式電感           | 6.0*2.5   | 0.2           | 20           | 163            | ±0%    |
| 3913    | TC-200M-3A-5026      | 中空圓環繞線式電感           | 15.0*7.0  | 3.0           | 20           | 17.6           | ±0%    |
| 3904    | TC-220M-2A-3726      | 中空圓環繞線式電感           | 12.0*6.0  | 2             | 22           | 23.0           | ±0%    |
| 9961    | TC-221M-2A-9426      | 中空圓環繞線式電感           | 28*12     | 2A            | 220          | 84.5           | ±0%    |
| 3853    | TC-240M-1A-3726      | 中空圓環繞線式電感           | 11.0*5.0  | 1.0           | 24           | 49.2           | ±0%    |
| 3914    | TC-241M-0.5A-3726    | 中空圓環繞線式電感           | 11.0*5.0  | 0.5           | 240          | 288            | ±0%    |
| 9967    | TC-251M-10A-13026    | 中空圓環繞線式電感           | 40*20     | 10A           | 250          | 20             | ±0%    |
| 3906    | TC-270M-0.3A-2026    | 中空圓環繞線式電感           | 6.0*3.0   | 0.3           | 27           | 104.6          | ±0%    |
| 9968    | TC-300M-10A-10626    | 中空圓環繞線式電感           | 34*17     | 10A           | 30           | 6.3            | ±0%    |
| 9962    | TC-301M-5A-9426      | 中空圓環繞線式電感           | 28*13     | 5A            | 300          | 49.2           | ±0%    |
| 2144    | TC-321M-5A-9026      | 中空圓環繞線式電感           | 27*14     | 5             | 320          | 52.5           | ±0%    |
| 12552   | TC-330M-4A-6026      | 中空圓環繞線式電感           | 27.2*7.5  | 4             | 33           |                | ±0%    |
| 9964    | TC-471M-1A-9026      | 中空圓環繞線式電感           | 25*11     | 1A            | 470          | 253            | ±0%    |
| 2146    | TC-471M-7A-13026     | 中空圓環繞線式電感           | 38*18     | 7A            | 470          | 49             | ±0%    |
| 3916    | TC-500M-5A-8026      | 中空圓環繞線式電感           | 24.0*10.0 | 5             | 50           | 19             | ±0%    |
| 9960    | TC-501M-3A-9426      | 中空圓環繞線式電感           | 28*13     | 3A            | 500          | 93.5           | ±0%    |
| 3907    | TC-5ROM-0.5A-2026    | 中空圓環繞線式電感           | 6.0*3.0   | 0.5           | 5            | 35.0           | ±0%    |
| 3852    | TC-680M-1A-3726      | 中空圓環繞線式電感           | 11.0*5.5  | 1.0           | 68           | 79             | ±0%    |
| 9971    | TC-681M-5A-13026     | 中空圓環繞線式電感           | 38*17     | 5A            | 680          | 80.4           | ±0%    |
| 9970    | TC-750M-10A-13026    | 中空圓環繞線式電感           | 40*17     | 10A           | 75           | 11.3           | ±0%    |
| 27745   | TC-BIF#26 x21T-16128 |                     |           | 1.5A          | 2.5mH        | 68m            |        |
| 27743   | TCT-84UH-45153-T     | EMI LINE FUKTER-TCB |           | 250mA         | 84uH         |                |        |

## 繞線式晶片型電感 Wound Chip Inductors

詳細產品規格--請點擊 [www.100y.com.tw](http://www.100y.com.tw)



| PartNo. | ProductNo.      | Manuf. | Description | 電感值(uH) | 誤差值(%) | Qmin. | Testingfreq.(MHz) | RDC  | IDC(mA)max | Size         |
|---------|-----------------|--------|-------------|---------|--------|-------|-------------------|------|------------|--------------|
| 11260   | FLC32T-1R0K     |        | 繞線式晶片型電感    | 1uH     | 10     | 30    | 7.96              | 0.7  | 400        | 322522(1210) |
| 11261   | JWI-322522-220K |        | 繞線式晶片型電感    | 2.2     | 10     | 30    | 2.52              | 3.7  | 110        | 322522(1210) |
| 13534   | JWI322522-101K  | JANTEK | 繞線式晶片型電感    | 100     | 10     | 20    | 0.796             | 11   | 40         | 32*25*22     |
| 13533   | JWI322522-121K  | JANTEK | 繞線式晶片型電感    | 120     | 10     | 20    | 0.796             | 12   | 70         | 32*25*22     |
| 13532   | JWI322522-151K  | JANTEK | 繞線式晶片型電感    | 150     | 10     | 20    | 0.796             | 15   | 65         | 32*25*22     |
| 13531   | JWI322522-181K  | JANTEK | 繞線式晶片型電感    | 180     | 10     | 20    | 0.796             | 17   | 60         | 32*25*22     |
| 13539   | JWI322522-1R0K  | JANTEK | 繞線式晶片型電感    | 1.0     | 10     | 30    | 7.96              | 0.7  | 400        | 32*25*22     |
| 13530   | JWI322522-221K  | JANTEK | 繞線式晶片型電感    | 220     | 10     | 20    | 0.796             | 21   | 50         | 32*25*22     |
| 13538   | JWI322522-330K  | JANTEK | 繞線式晶片型電感    | 3.3     | 10     | 30    | 2.52              | 5.6  | 70         | 32*25*22     |
| 13537   | JWI322522-470K  | JANTEK | 繞線式晶片型電感    | 4.7     | 10     | 30    | 2.52              | 7    | 60         | 32*25*22     |
| 13536   | JWI322522-560K  | JANTEK | 繞線式晶片型電感    | 5.6     | 10     | 30    | 2.52              | 8    | 55         | 32*25*22     |
| 13535   | JWI322522-680K  | JANTEK | 繞線式晶片型電感    | 6.8     | 10     | 30    | 2.52              | 9    | 50         | 32*25*22     |
| 13543   | JWI322522-R22M  | JANTEK | 繞線式晶片型電感    | 22      | 20     | 30    | 25.2              | 0.32 | 450        | 32*25*22     |
| 13542   | JWI322522-R33M  | JANTEK | 繞線式晶片型電感    | 33      | 20     | 30    | 25.2              | 0.4  | 450        | 32*25*22     |
| 13541   | JWI322522-R47M  | JANTEK | 繞線式晶片型電感    | 47      | 20     | 30    | 25.2              | 0.5  | 450        | 32*25*22     |
| 13540   | JWI322522-R68M  | JANTEK | 繞線式晶片型電感    | 68      | 20     | 30    | 25.2              | 0.6  | 450        | 32*25*22     |
| 13549   | JWI453232-101K  | JANTEK | 繞線式晶片型電感    | 100     | 10     | 40    | 0.796             | 8    | 110        | 45*32*32     |

