

**Description:**

24 AWG stranded tinned copper, Datalene. insulation, twisted pairs, overall Beldenfoil. Shielded plus a 24 AWG TC drain wire, PVC jacket

**PHYSICAL CHARACTERISTICS:****CONDUCTOR:**

Number of Conductors: 2  
Conductor Stranding : 7X0.20mm  
Conductor Material : TC – Tinned Copper

**INSULATION:**

Insulation Material : FPE-Foam polyethylene  
Nom. Insulation Diameter of : 1.25 mm

**TWIST PAIRS:**

Twist Lay Length : 32 mm

**OVERALL CABLING:**

Overall Cabling Lay Length : 76 mm

Overall Cabling Color Code Chart:

Pair Number Color

1 White /Blue Ring \* Blue /White Ring

2 White /Orange Ring \* Orange /White Ring

Overall Shield Trade Name : Beldenfoil.

Overall Shield Type : Tape

Overall Shield Material : Aluminum Foil-Polyester Tape w/S-Fold

Overall Shield Coverage (%) : 100

Drain Wire Conductor Material : TC – Tinned Copper

Drain Wire Conductor AWG : 24

Drain Wire Conductor Stranding : 7X0.20mm

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)