

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
 Http://www.100y.com.tw

**WIRE/CABLE SPECIFICATION (線材規格書)**

Standard		UL1332 16AWG 200°C 300V			
Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)	
General Specification (線種規格)		AWG	16		
No. of Inner Cords (芯線數)		PCs	1		
芯線結構	Conductor 導體	Material (材質)	-----	Tinned Copper	
		Structure (結構)	No.×mm	19 x 0.29	
		Stranded Diameter (絞線外徑)	mm	1.51	±0.1
	Insulation 絕緣	Material (材質)	-----	Teflon	
		Average Thickness (平均厚度)	mm	0.33	±0.1
		Color (顏色)	-----	----	
Overall Outer Diameter (最後完成外徑)		mm	2.17	±0.15	
Electric Characters 電氣特性	Rated Temperature (額定溫度)		°C	200	
	Rated Voltage (額定電壓)		V-DC	300	
	Resistance of Insulation (水中常溫絕緣電阻)		MΩ/km	50	
	Withstand Voltage Spark (火花試驗)		KV/Sec	1.5	
Marking		N/A			
Certification		N/A			

*Structural Configuration (結構圖):*

