



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

GREEN WIRE FOR OUR EARTH

WIRE/CABLE SPECIFICATION (線材規格書)

Standard		RSGE 0.75SQMM 200°C 300V			
Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)	
General Specification (線種規格)		SQMM	0.75		
芯線結構	Conductor 導體	Material (材質)	-----	Tinned Copper	
		Structure (結構)	No.×mm	30 / 0.18	
		Stranded Diameter (絞線外徑)	mm	1.19	±0.05
	Insulation 絕緣	Material (材質)	-----	Silicone Rubber	
		Average Thickness (平均厚度)	mm	0.76	±0.05
		Color (顏色)	-----	White	
	Braid 編織	Material (材質)	-----	Fiberglass	
		Color (顏色)	-----	White	
		Wall Thickness (壁厚)	mm	0.15	±0.02
Overall Outer Diameter (最後完成外徑)		mm	3.01	±0.15	
Electric Characters 電氣特性	Rated Temperature (額定溫度)		°C	200	
	Rated Voltage (額定電壓)		V-AC	300	
	Conductor Resistance of Insulation (導體阻抗, 20°C)		Ω/km	27.6	
	Withstand Voltage Spark (火花試驗)		KV/Sec	2	

適用領域/ Product Application

適用於家用電器、照明燈具、電子設備、溫度傳感器等引出連接線。

The wire can be used in various thermal places ranging from household appliances, lighting devices, industrial machines, to high-temperature furnace.

Marking	N/A
Certification	PSE JET5972-11001-1001

