



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

GREEN WIRE FOR OUR EARTH

WIRE/CABLE SPECIFICATION (線材規格書)

Standard

RSGE 1.25SQMM 200°C 300V

Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)	
General Specification (線種規格)		SQMM	1.25		
芯線結構	Conductor 導體	Material (材質)	Tinned Copper		
		Structure (結構)	No.×mm	50 / 0.18	
		Stranded Diameter (絞線外徑)	mm	1.50	±0.05
	Insulation 絕緣	Material (材質)	Silicone Rubber		
		Average Thickness (平均厚度)	mm	0.45	±0.05
		Color (顏色)	White		
	Braid 編織	Material (材質)	Fiberglass		
		Wall Thickness (壁厚)	mm	0.16	±0.02
Color (顏色): White、Red、Black、Blue、Brown、Yellow、Green、Yellow/Green					
Overall Outer Diameter (最後完成外徑)		mm	2.72	±0.1	
Electric Characters 電氣特性	Rated Temperature (額定溫度)	°C	200		
	Rated Voltage (額定電壓)	V-AC	300		
	Resistance of Insulation (水中常溫絕緣阻抗)	MΩ/km	50		
	Withstand Voltage Spark (火花試驗)	KV/Sec	2		
Certification	N/A				

Product Application (產品應用)

The wire can be used in various thermal places ranging from household appliances, lighting devices, industrial machines, to high-temperature furnace.

適用於各種家用電器, 照明燈具, 工業機器, 電熱製品, 原料溶爐等, 高溫場所之配線

Structural Configuration (結構圖):

