


CABLE NAME		30AWG(7/0.1SC)		CONSTRUCT																			
ITEM		SPECS																					
CONDUCTOR	Norm. Area.	30AWG			Insulation																		
	Material	Silver Plated copper			Conductor																		
	Size	7/0.1±0.005mm																					
	O.D(Ref)	0.3mm																					
INSULATION	Material	Teflon		<b>COLOR</b>																			
	Min. Average Thickness	0.175mm																					
	Min. Thickness at any Point	0.16mm		<b>MARKING</b>																			
	O.D	0.65±0.05mm																					
				<b>REMARK</b>																			
	<div style="border: 2px solid red; padding: 5px; color: red;">           勝特力材料 886-3-5753170            勝特力电子(上海) 86-21-34970699            勝特力电子(深圳) 86-755-83298787            Http://www.100y.com.tw         </div>																						
<b>ELECTRICAL DATA</b>		<b>PHYSICAL PROPERTIES</b>		<b>UNITPOWER</b>																			
1.Rated temperature:250℃ 2.Rated voltage:300V 3.Max. resistance of conductor(20℃):361 Ω /km 4.Voltage-withstand test:2.0kV/1min. 5.Spark test:3.0kV		1.Tensile strength: ≥10.3N/mm <sup>2</sup> Elongaion: ≥150% Aged(250±2℃×48h) Percent of tensile strength: ≥70% Percent of elongation: ≥65% 2.Flammability test:passes FT1.		<table border="1"> <thead> <tr> <th colspan="4">SPECS SHEET</th> </tr> </thead> <tbody> <tr> <td>APPROVED</td> <td>LIHUI</td> <td>CUSTOMER</td> <td></td> </tr> <tr> <td>CHECKED</td> <td>LINDA</td> <td>PART. NO.</td> <td></td> </tr> <tr> <td>DRAWN</td> <td>LINDA</td> <td>DATE</td> <td>20141125</td> </tr> </tbody> </table>				SPECS SHEET				APPROVED	LIHUI	CUSTOMER		CHECKED	LINDA	PART. NO.		DRAWN	LINDA	DATE	20141125
SPECS SHEET																							
APPROVED	LIHUI	CUSTOMER																					
CHECKED	LINDA	PART. NO.																					
DRAWN	LINDA	DATE	20141125																				