


CABLE NAME		UL1332 16AWG(19/0.30TS)		CONSTRUCT																			
ITEM		SPECS																					
CONDUCTOR	Norm. Area.	1.35MM2		 <p>Insulation Conductor</p>																			
	Material	Tinned copper																					
	Size	19/0.30+/-0.008mm																					
	O.D(Ref)	1.50mm																					
INSULATION	Material	FEP(-60--200℃)																					
	Min. Average Thickness	0.35mm		BY ORDER																			
	Min. Thickness	0.33mm																					
	O.D	2.15±0.10mm																					
				MARKING																			
				REMARK																			
				Referance standardUL1332																			
ELECTRICAL DATA		PHYSICAL PROPERTIES		UNITPOWER																			
1.Rated temperature:200℃ 2.Rated voltage:300V 3.Max. resistance of conductor(20℃):14 Ω /km 4.Voltage-withstand test:2.0kV/1min. 5.Spark test:3.0kV		1.Tensile strength: ≥10.3N/mm ² Elongaion: ≥150% Aged(250±2℃×48h) Percent of tensile strength: ≥70% Percent of elongation: ≥65% 2.Flammability test:passes FT1.		<table border="1"> <thead> <tr> <th colspan="4">SPECS SHEET</th> </tr> </thead> <tbody> <tr> <td>APPROVED</td> <td>LIHUI</td> <td>CUSTOMER</td> <td></td> </tr> <tr> <td>CHECKED</td> <td>LINDA</td> <td>PART. NO.</td> <td>1213-16</td> </tr> <tr> <td>DRAWN</td> <td>LINDA</td> <td>DATE</td> <td>2012.04.25</td> </tr> </tbody> </table>				SPECS SHEET				APPROVED	LIHUI	CUSTOMER		CHECKED	LINDA	PART. NO.	1213-16	DRAWN	LINDA	DATE	2012.04.25
SPECS SHEET																							
APPROVED	LIHUI	CUSTOMER																					
CHECKED	LINDA	PART. NO.	1213-16																				
DRAWN	LINDA	DATE	2012.04.25																				
<div style="border: 2px solid red; padding: 5px;"> <p>勝特力材料 886-3-5753170 勝特力电子(上海) 86-21-34970699 勝特力电子(深圳) 86-755-83298787 Http://www.100y.com.tw</p> </div>																							