

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

GREEN WIRE FOR OUR EARTH

WIRE/CABLE SPECIFICATION (線材規格書)

Standard		UL1332 26AWG 200°C 300V		
Item (項目)		Unit (單位)	Specification (規格值)	Tolerance (容差)
General Specification (線種規格)		AWG	26	
芯線結構	Conductor 導體	Material (材質)	Tinned Copper	
		Structure (結構)	No.×mm	7 / 0.16
		Stranded Diameter (絞線外徑)	mm	0.50
	Insulation 絕緣	Material (材質)	Teflon	
		Average Thickness (平均厚度)	mm	0.33
Color (顏色): White、Red、Black、Blue、Brown、Yellow、Green、Yellow/Green				
Overall Outer Diameter (最後完成外徑)		mm	1.16	±0.1
Electric Characters 電氣特性	Rated Temperature (額定溫度)		°C	200
	Rated Voltage (額定電壓)		V-AC	300
	Resistance of Insulation (水中常溫絕緣阻抗)		MΩ/km	1000
	Withstand Voltage Spark (火花試驗)		KV/Sec	2
Flame Retardant (耐燃)		-----	VW-1	PASS
Marking	E215834 c兄us AWM STYLE 1332 FEP 200°C 300V 26AWG VW-1 NIZING ELECTRIC CSA AWM IA 200°C 300V FT1 26AWG LF			
Certification	AWM UL1332 E215834			

Product Application (產品應用)

適用於各種家用電器, 照明燈具, 工業機器, 電熱製品, 原料溶爐等高溫場所之配線

The wire can be used in various thermal places ranging from household appliances, lighting devices, industrial machines, to high-temperature furnace.

