

TYPE:MMT

MMT is a micro-miniature capacitor in stacked construction composed of ultra-thin metallized polyester film made available by our unique engineering method to meet the needs of miniaturization.

FEATURES:

- 5.0mm(.200") lead spacing on all values.
- Space-saving miniature size.
- Self-healing property.
- High moisture resistance.
- Good solderability.
- Available on tape and reel for automatic insertion.


勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

APPLICATIONS:

They are ideal for telecommunication equipments, data processing equipments, industrial instruments, automatic control systems and other general electronic equipments.

SPECIFICATION:

- | | |
|-------------------------------|---|
| 1. Operating temperature | : -40°C ~ +85°C |
| 2. Capacitance range | : .01uF ~ 1.0uF |
| 3. Capacitance tolerance | : J=±5%, K=±10%, M=±20%. |
| 4. Rated voltage (RV) | : 50/63/100VDC |
| 5. Dissipation factor (DF) | : 1.0% max at 1KHz 25°C |
| 6. Insulation resistance (IR) | : C ≤ .33uF and IR ≥ 10000MΩ
C > .33uF and IR ≥ 3000MΩ .uF |



DIMENSIONS:

unit:mm

RV		50/63/100VDC				
CODE	SIZE	W	H	T	P	dφ
	Cap(uF)					
103-823	0.01-0.082	8.0	5.0	3.2	5.0	0.5
104	0.1	8.0	5.0	3.2	5.0	0.5
124	0.12	8.0	5.0	3.2	5.0	0.5
154	0.15	8.0	5.5	3.5	5.0	0.5
184	0.18	8.0	5.5	5.0	5.0	0.5
224	0.22	8.0	5.5	3.8	5.0	0.5
274	0.27	8.0	6.5	4.3	5.0	0.5
334	0.33	8.0	6.5	4.5	5.0	0.5
394	0.39	8.0	7.0	5.0	5.0	0.5
474	0.47	8.0	8.0	5.0	5.0	0.5
564	0.56	8.0	10.0	4.3	5.0	0.5
684	0.68	8.0	10.0	4.5	5.0	0.5
824	0.82	8.0	11.0	5.0	5.0	0.5
105	1.0	8.0	11.0	5.3	5.0	0.5