


**Interference Suppression Film Capacitors  
MKP Radial Potted Type**



Dimensions in mm  
 $|F - F'| < 0.3 \text{ mm}$   
 $F = 7.5 + 0.6/-0.1 \text{ mm}$

**NO FOCUS PRODUCT: USE MKP 339 X2**

**APPLICATIONS**

X2 class

For X2 electromagnetic interference suppression in across the line applications (50/60 Hz) with a maximum mains voltage of 275 Vac.

For application limitations please refer page 14.

**REFERENCE STANDARDS**

“IEC 60384-14 2nd edition and EN 132400”  
 “IEC 60065 requires pass flamm class B”  
 250 V: UL1414; CSA-C22.2 No 1  
 275 V: CSA-C22.2 No 8 ENEC; CQC  
 305 V: UL1283

**MARKING**

C-value; tolerance; rated voltage; sub-class; manufacturer’s type designation; code for dielectric material, manufacturer location; manufacturer’s emblem; year and week

**DIELECTRIC**

Polypropylene film

**ELECTRODES**

Metallized film

**CONSTRUCTION**

Mono construction

**RATED VOLTAGE**

AC 275 V; 50 to 60 Hz

**FEATURES**

7.5 to 27.5 mm lead pitch. Supplied in box, taped on ammpack or reel

Lead (Pb)-free product

RoHS-compliant product



**RoHS**  
COMPLIANT

**PERMISSIBLE DC VOLTAGE**

DC 630 V

**ENCAPSULATION**

Plastic case, epoxy resin sealed, flame retardant UL-class 94 V-0

**CLIMATIC TESTING CLASS ACC. TO EN 60068-1**

55/110/56/B

**CAPACITANCE RANGE (E12 SERIES)**

E12 series 0.001 to 3.3  $\mu\text{F}$   
 Preferred values acc. to E6

**CAPACITANCE TOLERANCE**

$\pm 20 \%$ ;  $\pm 10 \%$ ;  $\pm 5 \%$

**LEADS**

Tinned wire

**MAXIMUM APPLICATION TEMPERATURE**


110 °C

**DETAIL SPECIFICATION**

For more detailed data and test requirements contact:  
[RFI@vishay.com](mailto:RFI@vishay.com)



**COMPOSITION OF CATALOG NUMBER**



TYPE	PACKAGING	STANDARD DIMENSIONS	C-TOL	PREFERRED TYPES	
338 2 X2	loose in box	lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 20 %	BFC2 338 20...	
		lead length 5.0 ± 1.0 mm		BFC2 338 22...	
		lead length 25.0 ± 2.0 mm		BFC2 338 24...	
	taped	Pitch 7.5 mm or bent back to 7.5 mm			BFC2 338 26...
	<b>PACKAGING</b>	<b>ALTERNATIVE LARGER PITCH SIZES</b>			<b>ON REQUEST</b>
	loose in box		lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 20 %	see tables for details
			lead length 5.0 ± 1.0 mm		
			lead length 25.0 ± 2.0 mm		
	<b>PACKAGING</b>	<b>ALTERNATIVE TAPED VERSION<sup>(1)</sup></b>			<b>ON REQUEST</b>
	taped		H = 18.5 mm; P <sub>0</sub> = 12.7 mm <sup>(2)</sup>	± 20 %	see tables for details
	<b>PACKAGING</b>	<b>ALTERNATIVE C-TOL</b>			<b>ON REQUEST</b>
	loose in box		lead length 3.5 + 1/- 0.5 mm or 3.5 ± 0.3 mm	± 10 % ± 5 %	see tables for details
		lead length 5.0 ± 1.0 mm	± 10 % ± 5 %		
		lead length 25.0 ± 2.0 mm	± 10 % ± 5 %		
taped		pitch 7.5 mm or bent back to 7.5 mm	± 10 % ± 5 %		
		H = 18.5 mm; P <sub>0</sub> = 12.7 mm	± 10 % ± 5 %		

**Notes**

1. Taped on reel pitch = 27.5 mm is not available
2. For detailed tape specifications refer to "Packaging information" [www.vishay.com/docs/28139/packinfo.pdf](http://www.vishay.com/docs/28139/packinfo.pdf)

**SPECIFIC REFERENCE DATA FOR THE 275 V AC (X2) CAPACITORS**

DESCRIPTION	VALUE	
	at 1 kHz	at 10 kHz
Tangent of loss angle:		
C ≤ 470 nF	≤ 10 × 10 <sup>-4</sup>	≤ 20 × 10 <sup>-4</sup>
470 nF < C ≤ 1 μF	≤ 20 × 10 <sup>-4</sup>	≤ 70 × 10 <sup>-4</sup>
C > 1 μF	≤ 30 × 10 <sup>-4</sup>	-
Rated voltage pulse slope (dU/dt) <sub>R</sub> at 385 V (DC)	100 V/μs	
R between leads, for C ≤ 0.33 μF at 100 V; 1 minute	> 15 000 MΩ	
RC between leads, for C > 0.33 μF at 100 V; 1 minute	> 5000 s	
R between leads and case; 100 V; 1 minute	> 30 000 MΩ	
Withstanding (DC) voltage (cut off current 10 mA); rise time 100 V/s:		
C ≤ 1 μF	2200 V; 1 min	
C > 1 μF	1800 V; 1 min	
Withstanding (AC) voltage between leads and case	2050 V; 1 min	
Maximum application temperature	110 °C	

Vishay BCcomponents Interference Suppression Film Capacitors  
MKP Radial Potted Type

Pitch: 7.5 mm; C-tol = ± 20 % (for reference:  $U_{Rdc} = 630 V$ )

$U_{Rac} = 275 V$

C ( $\mu F$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$3.5 + 1/- 0.5$ mm	$5.0 \pm 1.0$ mm	SPQ	$25.0 \pm 2.0$ mm	SPQ		SPQ
Pitch = 7.5 ± 0.4 mm; d <sub>t</sub> = 0.50 ± 0.05 mm									
0.001	4.0 × 9.0 × 10.0	0.4	20102	22102		24102		26102	
0.0012			20122	22122		24122		26122	
0.0015			20152	22152		24152		26152	
0.0018			20182	22182		24182		26182	
0.0022			20222	22222		24222		26222	
0.0027			20272	22272		24272		26272	
0.0033			20332	22332		24332		26332	
0.0039			20392	22392		24392		26392	
0.0047			20472	22472	1500	24472	1000	26472	1250
0.0056			20562	22562		24562		26562	
0.0068			20682	22682		24682		26682	
0.0082			20822	22822		24822		26822	
0.01			20103	22103		24103		26103	
0.012			20123	22123		24123		26123	
0.015			20153	22153		24153		26153	
0.018			20183	22183		24183		26183	
0.022			20223	22223		24223		26223	
0.027			20273	22273	1000	24273	1250	26273	1000
0.033	20333	22333		24333		26333			
0.039	20393	22393	750	24393	1000	26393	750		
0.047	20473	22473		24473		26473			

Note

1. Weight for short lead product only

Pitch: 7.5 mm; C-tol = ± 10 % (for reference:  $U_{Rdc} = 630 V$ )

$U_{Rac} = 275 V$

C ( $\mu F$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$3.5 + 1/- 0.5$ mm	$5.0 \pm 1.0$ mm	SPQ	$25.0 \pm 2.0$ mm	SPQ		SPQ
Pitch = 7.5 ± 0.4 mm; d <sub>t</sub> = 0.50 ± 0.05 mm									
0.001	4.0 × 9.0 × 10.0	0.4	28101	28301		28501		28701	
0.0012			28102	28302		28502		28702	
0.0015			28103	28303		28503		28703	
0.0018			28104	28304		28504		28704	
0.0022			28105	28305		28505		28705	
0.0027			28106	28306		28506		28706	
0.0033			28107	28307		28507		28707	
0.0039			28108	28308		28508		28708	
0.0047			28109	28309	1500	28509	1000	28709	1250
0.0056			28111	28311		28511		28711	
0.0068			28112	28312		28512		28712	
0.0082			28113	28313		28513		28713	
0.01			28114	28314		28514		28714	
0.012			28115	28315		28515		28715	
0.015			28116	28316		28516		28716	
0.018			28117	28317		28517		28717	
0.022			28118	28318		28518		28718	
0.027			28119	28319	1000	28519	1250	28719	1000
0.033	28121	28321		28521		28721			
0.039	28122	28332	750	28522	1000	28722	750		
0.047	28123	28323		28523		28723			



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

Pitch: 7.5 mm; C-tol = ± 5 % (for reference: U<sub>Rdc</sub> = 630 V)

U<sub>Rac</sub> = 275 V

C (µF)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING								
			LOOSE IN BOX					AMMOPACK			
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm			
			3.5 + 1/-0.5 mm <sup>(2)</sup>	5.0 ± 1.0 mm	SPQ	25.0 ± 2.0 mm	SPQ		SPQ		
<b>Pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.50 ± 0.05 mm</b>											
0.001	4.0 x 9.0 x 10.0	0.4	28201	28401		28601		28801	1250		
0.0012			28202	28402		28602		28802			
0.0015			28203	28403		28603		28803			
0.0018			28204	28404		28604		28804			
0.0022			28205	28405		28605		28805			
0.0027			28206	28406		28606		28806			
0.0033			28207	28407		28607		28807			
0.0039			28208	28408	1500	28608	1000	28808			
0.0047			28209	28409		28609		28809			
0.0056			28211	28411		28611		28811			
0.0068			28212	28412		28612		28812			
0.0082			28213	28413		28613		28813			
0.01			28214	28414		28614		28814			
0.012			28215	28415		28615		28815			
0.015			28216	28416		28616		28816			
0.018			28217	28417		28617		28817			
0.022			28218	28418		28618		28818			
0.027			28219	28419		1000		28619		1250	28819
0.033	5.0 x 10.5 x 10.0	0.6	28221	28421		1000		28621	1250	28821	1000
0.039			28222	28422		750		28622	1000	28822	750
0.047	6.0 x 11.5 x 10.0	0.8	28223	28423		750		28623	1000	28823	750

Bent back pitch: 7.5 mm (only taped); C-tol = ± 20 % (for reference: U<sub>Rdc</sub> = 630 V)

C (µF)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(2)</sup>	CATALOG NUMBER BFC2 338 ..... AND PACKAGING	
			REEL (500 mm) <sup>(1)</sup>	
			H = 16.0 mm; P <sub>0</sub> = 15.0 mm	SPQ
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.056	5.0 x 13.0 x 12.5	0.82	26563	
0.068			26683	
0.082	6.0 x 14.0 x 12.5	1.1	26823	
0.1			26104	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.12	5.0 x 13.0 x 17.5	1.0	26124	
0.15	6.0 x 14.0 x 17.5	1.4	26154	
0.18			26184	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.22	7.0 x 15.5 x 17.5	1.8	26224	
0.27	8.5 x 17.0 x 17.5	2.4	26274	
0.33			26334	

Notes

1. Reel diameter = 356 mm is available on request
2. Weight for short lead product only

## Vishay BCcomponents Interference Suppression Film Capacitors MKP Radial Potted Type

**Bent back pitch: 7.5 mm (only taped); C-tol = ± 10 %** (for reference:  $U_{Rdc} = 630$  V)

C ( $\mu$ F)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(2)</sup>	CATALOG NUMBER BFC2 338 2 .....AND PACKAGING	
			REEL (500 mm) <sup>(1)</sup>	
			H = 16.0 mm; P <sub>0</sub> = 15.0 mm	SPQ
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.056	5.0 x 13.0 x 12.5	0.82	28724	1600
0.068			28725	
0.082			28726	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.1	5.0 x 13.0 x 17.5	1.0	28727	800
0.12	6.0 x 14.0 x 17.5	1.4	28728	700
0.15			28729	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.80 ± 0.08 mm</b>				
0.18	7.0 x 15.5 x 17.5	1.8	28731	550
0.22			28732	
0.27	8.5 x 17.0 x 17.5	2.4	28733	500
0.33			29168	

### Notes

1. Reel diameter = 356 mm is available on request
2. Weight for short lead product only

**Bent back pitch: 7.5 mm (only taped); C-tol = ± 5 %** (for reference:  $U_{Rdc} = 630$  V)

C ( $\mu$ F)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(2)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING	
			REEL (500 mm) <sup>(1)</sup>	
			H = 16.0 mm; P <sub>0</sub> = 15.0 mm	SPQ
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.056	6.0 x 14.0 x 12.5	1.1	28824	1600
0.068			28825	
0.082			28826	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.1	5.0 x 13.0 x 17.5	1.0	28827	800
0.12	6.0 x 14.0 x 17.5	1.4	28828	700
0.15			28829	
<b>Bent back pitch = 7.5 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>				
0.18	7.0 x 15.5 x 17.5	1.8	28831	550
0.22			28832	
0.27	8.5 x 17.0 x 17.5	2.4	28833	500

### Notes

1. Reel diameter = 356 mm is available on request
2. Weight for short lead product only



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

Pitch: 10.0 mm; C-tol = ± 20 % (for reference:  $U_{RDC} = 630 V$ )

$U_{Rac} = 275 V$

C (µF)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$3.5 + 1/- 0.5$ mm	$5.0 \pm 1.0$ mm	SPQ	$25.0 \pm 2.0$ mm	SPQ		SPQ
<b>Pitch = 10.0 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>									
0.001	4.0 x 10.0 x 12.5	0.6	21102	23102	1000	25102	1250	Not available	
0.0012			21122	23122		25122			
0.0015			21152	23152		25152			
0.0018			21182	23182		25182			
0.0022			21222	23222		25222			
0.0027			21272	23272		25272			
0.0033			21332	23332		25332			
0.0039			21392	23392		25392			
0.0047			21472	23472		25472			
0.0056			21562	23562		25562			
0.0068			21682	23682		25682			
0.0082			21822	23822		25822			
0.01			21103	23103		25103			
0.012			21123	23123		25123			
0.015			21153	23153		25153			
0.018			21183	23183		25183			
0.022			21223	23223		25223			
0.027			21273	23273		25273			
0.033			21333	23333		25333			
0.039			21393	23393		25393			
0.047	21473	23473	25473						
0.056	5.0 x 11.0 x 12.5	0.82	20563	22563	750	24563	750	27563	500
0.068			20683	22683		24683		27683	
0.082	6.0 x 12.0 x 12.5	1.1	20823	22823	750	24823	750	27823	500
0.1			20104	22104		24104		27104	

**Note**

1. Weight for short lead product only

Pitch: 10.0 mm; C-tol = ± 10 % (for reference:  $U_{RDC} = 630 V$ )

$U_{Rac} = 275 V$

C (µF)	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$3.5 + 1/- 0.5$ mm	$5.0 \pm 1.0$ mm	SPQ	$25.0 \pm 2.0$ mm	SPQ		SPQ
<b>Pitch = 10.0 ± 0.4 mm; d<sub>t</sub> = 0.60 ± 0.06 mm</b>									
0.001	4.0 x 10.0 x 12.5	0.6	29194	29217	1000	29241	1250	Not available	
0.0012			29195	29218		29242			
0.0015			29196	29219		29243			
0.0018			29197	29221		29244			
0.0022			29198	29222		29245			
0.0027			29199	29223		29246			
0.0033			29201	29224		29247			
0.0039			29202	29225		29248			
0.0047			29203	29226		29249			
0.0056			29204	29227		29251			

## Vishay BCcomponents Interference Suppression Film Capacitors MKP Radial Potted Type

Pitch: 10.0 mm; C-tol = ± 10 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t =$ 3.5 + 1/- 0.5 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
0.0068	4.0 x 10.0 x 12.5	0.6	29205	29228	1000	29252	1000	Not available	
0.0082			29206	29229		29253			
0.01			29207	29231		29254			
0.012			29208	29232		29255			
0.015			29209	29233		29256			
0.018			29211	29234		29257			
0.022			29212	29235		29258			
0.027			29213	29236		29259			
0.033			29214	29237		29261			
0.039			29215	29238		29262			
0.047	29216	29239	29263						
0.056	5.0 x 11.0 x 12.5	0.82	28124	28324	750	28524	750	28924	500
0.068			28125	28325		28525		28925	
0.082	6.0 x 12.0 x 12.5	1.1	28126	28326	750	28526	750	28926	500

**Note**

1. Weight for short lead product only

Pitch: 10.0 mm; C-tol = ± 5 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					AMMOPACK	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t =$ 3.5 + 1/- 0.5 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
<b>Pitch = 10.0 ± 0.4 mm; <math>d_t = 0.60 \pm 0.06\text{ mm}</math></b>									
0.056	5.0 x 11.0 x 12.5	0.82	28224	28424	750	28624	750	28944	500
0.068	6.0 x 12.0 x 12.5	1.1	28225	28425	750	28625	750	28945	500
0.082			28226	28426		28626		28946	

**Note**

1. Weight for short lead product only

Pitch: 15.0 mm; C-tol = ± 20 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm)	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ
<b>Pitch = 15 ± 0.4 mm; <math>d_t = 0.60 \pm 0.06\text{ mm}</math></b>									
0.01	5.0 x 11.0 x 17.5	1.0	29076	29096	1000	29116	1000	29141	1100
0.012			29077	29097		29117		29143	
0.015			29078	29098		29118		29145	
0.018			29079	29099		29119		29147	
0.022			29081	29101		29121		29149	
0.027			29082	29102		29122		29152	
0.033			29083	29103		29123		29154	
0.039			29084	29104		29124		29156	



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

Pitch: 15.0 mm; C-tol = ± 20 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING									
			LOOSE IN BOX					REEL (500 mm)				
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm				
			$l_t =$ 3.5 ± 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ			
0.047	6.0 x 12.0 x 17.5	1.0	29085	29105	1000	29125	1000	29158	1100			
0.056			21563	23563		25563		29161				
0.068			21683	23683		25683		29163				
0.082			21823	23823		25823		29165				
0.1			21104	23104		25104		29166				
0.12			20124	22124		1000		24124		1000	27124	900
0.15			20154	22154		750		24154		500	27154	800
0.18	20184	22184		24184		27184						
<b>Pitch = 15 ± 0.4 mm; <math>d_t = 0.80 \pm 0.08\text{ mm}</math></b>												
0.22	7.0 x 13.5 x 17.5	1.8	20224	22224	750	24224	500	27224	650			
0.27	8.5 x 15.0 x 17.5	2.4	20274	22274	750	24274	500	27274	650			
0.33			20334	22334	500	24334	450	27334	600			

**Note**

- Weight for short lead product only

Pitch: 15.0 mm; C-tol = ± 10 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING									
			LOOSE IN BOX					REEL (500 mm)				
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm				
			$l_t =$ 3.5 + 1/- 0.3 mm	$l_t =$ 5.0 ± 1.0 mm	SPQ	$l_t =$ 25.0 ± 2.0 mm	SPQ		SPQ			
<b>Pitch = 15 ± 0.4 mm; <math>d_t = 0.60 \pm 0.06\text{ mm}</math></b>												
0.01	5.0 x 11.0 x 17.5	1.0	29066	29086	1000	29106	1000	29139	1100			
0.012			29067	29087		29107		29142				
0.015			29068	29088		29108		29144				
0.018			29069	29089		29109		29146				
0.022			29071	29091		29111		29148				
0.027			29072	29092		29112		29151				
0.033			29073	29093		29113		29153				
0.039			29074	29094		29114		29155				
0.047			29075	29095		29115		29157				
0.056			29126	29131		29135		29159				
0.068			29127	29132		29136		29162				
0.082			29128	29133		29137		29164				
0.1			28127	28327		1000		28527		1000	28927	900
0.12			6.0 x 12.0 x 17.5	1.4		28128		28328		750	28528	500
0.15	28129	28329				28529		28929				
<b>Pitch = 15 ± 0.4 mm; <math>d_t = 0.80 \pm 0.08\text{ mm}</math></b>												
0.18	7.0 x 13.5 x 17.5	1.8	28131	28331	750	28531	500	28931	650			
0.22			28132	28332		28532		28932				
0.27	8.5 x 15.0 x 17.5	2.4	28133	28333	500	28533	450	28933	600			
0.33			29129	29134		29138		29167				

**Note**

- Weight for short lead product only



# MKP 338 2 X2



## Vishay BCcomponents Interference Suppression Film Capacitors MKP Radial Potted Type

Pitch: 15.0 mm; C-tol = ± 5 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm)	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t = 3.5 \pm 1/- 0.3\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ		SPQ
Pitch = 15 ± 0.4 mm; $d_t = 0.60 \pm 0.06\text{ mm}$									
0.1	5.0 x 11.0 x 17.5	1.0	28227	28427	1000	28627	1000	28947	900
0.12	6.0 x 12.0 x 17.5	1.4	28228	28428	750	28628	500	28948	800
0.15			28229	28429		28629		28949	
Pitch = 15 ± 0.4 mm; $d_t = 0.80 \pm 0.08\text{ mm}$									
0.18	7.0 x 13.5 x 17.5	1.8	28231	28431	750	28631	500	28951	650
0.22	8.5 x 15.0 x 17.5	2.4	28232	28432	750	28632	500	28952	650
0.27			28233	28433		28633		450	

**Note**

1. Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 20 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm)	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ		SPQ
Pitch = 22.5 ± 0.4 mm; $d_t = 0.80 \pm 0.08\text{ mm}$									
0.12	6.0 x 15.5 x 26.0	2.4	21124	23124	300	25124	250	29264	600
0.15			21154	23154		25154		29265	
0.18			21184	23184	200	25184	250	29266	500
0.22			21224	23224		25224		29267	
0.27			21274	23274		25274		29268	
0.33	21334	23334		25334		29269			
0.39	7.0 x 16.5 x 26.0	2.9	20394	22394	200	24394	250	27394	450
0.47			20474	22474		24474		27474	
0.56	8.5 x 18.0 x 26.0	3.8	20564	22564	200	24564	200	27564	350
0.68			20684	22684		24684		27684	
0.82	10.0 x 19.5 x 26.0	6.8	20824	22824	150	24824	200	27824	300
1.0			20105	22105		24105		27105	

**Note**

1. Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 10 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING						
			LOOSE IN BOX					REEL (500 mm)	
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm	
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ		SPQ
Pitch = 22.5 ± 0.4 mm; $d_t = 0.80 \pm 0.08\text{ mm}$									
0.12	6.0 x 15.5 x 26.0	2.4	29169	29175	300	29181	250	29271	600
0.15			29171	29176		29182		29272	
0.18			29172	29177	200	29183	250	29273	500
0.22			29173	29178		29184		29274	
0.27			29174	29179		29185		29275	
0.33			28134	28334		28534		28934	450



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

Pitch: 22.5 mm; C-tol = ± 10 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING							
			LOOSE IN BOX				REEL (500 mm)			
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm		SPQ
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ			
0.39	7.0 x 16.5 x 26.0	2.9	28135	28335	200	28535	250	28935	450	
0.47			28136	28336		28536	200	28936		
0.56	8.5 x 18.0 x 26.0	3.8	28137	28337	150	28537		200	28937	300
0.68	10.0 x 19.5 x 26.0	6.8	28138	28338		28538	28938			
0.82			28139	28339	28539	28939				

**Note**

- Weight for short lead product only

Pitch: 22.5 mm; C-tol = ± 5 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING							
			LOOSE IN BOX				REEL (500 mm)			
			Short leads			Long leads		H = 18.5 mm P <sub>0</sub> = 12.7 mm		SPQ
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ			
<b>Pitch = 22.5 ± 0.4 mm; d<sub>t</sub> = 0.80 ± 0.08 mm</b>										
0.33	7.0 x 16.5 x 26.0	2.9	28234	28434	200	28634	250	28954	450	
0.39			28235	28435		28635	28955			
0.47	8.5 x 18.0 x 26.0	3.8	28236	28436	200	28636	200	28956	350	
0.56			28237	28437		28637	28957			
0.68	10.0 x 19.5 x 26.0	6.8	28238	28438	150	28638	200	28958	300	
0.82	12.0 x 22.0 x 26.0	7.8	28239	28439	150	28639	200	28959	300	

**Note**

- Weight for short lead product only

Pitch: 27.5 mm; C-tol = ± 20 % (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING					
			LOOSE IN BOX			REEL (500 mm)		
			Short leads			Long leads		SPQ
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ	
<b>Pitch = 27.5 ± 0.4 mm; d<sub>t</sub> = 0.80 ± 0.08 mm</b>								
0.39	9.0 x 19.0 x 31.0	5.5	21394	23394	100	25394	150	
0.47			21474	23474		25474		
0.56			21564	23564		25564		
0.68			21684	23684		25684		
0.82			21824	23824		25824		
1.0	11.0 x 21.0 x 31.0	7.4	21105	23105	100	25105	125	
1.2			20125	22125		24125		
1.5	13.0 x 23.0 x 31.0	9.2	20155	22155		100	24155	
1.8			20185	22185			24185	
2.2	15.0 x 25.0 x 31.0	12.3	20225	22225		50	24225	100
2.7	18.0 x 28.0 x 31.0	16.1	20275	22275	24275			
3.3			20335	22335	24335		75	

**Note**

- Weight for short lead product only

# MKP 338 2 X2



## Vishay BCcomponents Interference Suppression Film Capacitors MKP Radial Potted Type

Body length: 31.0 mm Pitch: 27.5 mm C-tol =  $\pm 10\%$  (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t = 3.5 \pm 0.5\text{ mm}^{(2)}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ
<b>Pitch = <math>27.5 \pm 0.4\text{ mm}</math>; <math>d_t = 0.80 \pm 0.08\text{ mm}</math></b>							
1.0	11.0 x 21.0 x 31.0	7.4	28141	28341	100	28541	125
1.2			28142	28342		28542	
1.5			28143	28343		28543	
1.8	15.0 x 25.0 x 31.0	12.3	28144	28344	50	28544	100
2.2			28145	28345		28545	75
2.7			28146	28346		28546	

**Note**

- Weight for short lead product only

Pitch: 27.5 mm; C-tol =  $\pm 5\%$  (for reference:  $U_{RDC} = 630\text{ V}$ )

$U_{Rac} = 275\text{ V}$

C ( $\mu\text{F}$ )	DIMENSIONS W x H x L (mm)	MASS (g) <sup>(1)</sup>	CATALOG NUMBER BFC2 338 2 ..... AND PACKAGING				
			LOOSE IN BOX				
			Short leads			Long leads	
			$l_t = 3.5 \pm 0.5\text{ mm}$	$l_t = 5.0 \pm 1.0\text{ mm}$	SPQ	$l_t = 25.0 \pm 2.0\text{ mm}$	SPQ
<b>Pitch = <math>27.5 \pm 0.4\text{ mm}</math>; <math>d_t = 0.80 \pm 0.08\text{ mm}</math></b>							
1	11.0 x 21.0 x 31.0	7.4	28241	28441	100	28641	125
1.2	13.0 x 23.0 x 31.0	9.2	28242	28442	100	28642	125
1.5			28243	28443		28643	
1.8	15.0 x 25.0 x 31.0	12.3	28244	28444	100	28644	100
2.2	18.0 x 28.0 x 31.0	16.1	28245	28445	50	28645	75
2.7			28246	28446		28646	

**Note**

- Weight for short lead product only

Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

SAFETY APPROVALS X2	VOLTAGE	VALUE	FILE NUMBERS
EN132400	275 V (AC)	1 nF to 3.3 $\mu$ F	FI 2006019
UL1414; CSA-C22.2 No.1	250 V (AC)	1 nF to 1 $\mu$ F	E112471
UL 1283	305 V (AC)	1 nF to 3.3 $\mu$ F	E109565
CSA-C22.2 No.8	275 V (AC)	1 nF to 3.3 $\mu$ F	1438188
CQC	275 V (AC)	1 nF to 3.3 $\mu$ F	CQC07001018685 (F) CQC03001004373 (R) CQC03001003071 (S)

The ENEC-Approval together with the CB-certificate replace all national marks of the following countries (they have already signed the ENEC-Agreement): Austria; Belgium; Czech. Republic; Denmark; Finland; France; Germany; Greece; Hungary; Ireland; Italy; Luxembourg; Netherlands; Norway; Portugal; Slovenian; Spain; Sweden; Switzerland; and United Kingdom.

**MOUNTING**
**NORMAL USE**

The capacitors are designed for mounting on printed -circuit boards. The capacitors packed in bandoliers are designed for mounting in pinte-circuit boards by means of automatic insertion machines. For detailed tape specifications refer to "Packaging information".

**SPECIFIC METHOD OF MOUNTING TO WITHSTAND VIBRATION AND SHOCK**


In order to withstand vibration and shock tests, it must be insured that the stand-off pips are in good contact with the printed circuit board:

- For pitches  $\leq 15$  mm capacitors shall be mechanically fixed by the leads
- For larger pitches the capacitors shall be mounted in the same way and the body clamped.

**SPACE REQUIREMENTS ON PRINTED CIRCUIT BOARD**

The maximum length and width of film capacitors is shown in the figure:

- Eccentricity as in figure. The maximum eccentricity is smaller than or equal to the product concerned
- Product height with seating plane as given by "IEC 60717" as reference:  $h_{max} \leq + 0.3$  mm or  $h_{max} \leq h + 0.3$  mm.


**STORAGE TEMPERATURE**


- Storage temperature:  $T_{stg} = - 25$  to  $+ 40$  °C with RH maximum 80 % without condensation

**CHACTERISTICS REFERENCE CONDITIONS**


Unless otherwise specified, all elctrical values apply to an ambient temperature of  $23 \pm 1$  °C, an atmospheric pressure of 86 to 106 kPa and a relative humidity of  $50 \pm 2$  %.

For reference testing, a conditioning period shall be applied over  $96 \pm 4$  hours by heating the products in a circulating air oven at the rated temperature and a relative humidity not exceeding 20 %.


## CHARACTERISTICS




## IMPEDANCE





## TANGET OF LOSS ANGLE



## RESONANT FREQUENCY




## MAX RMS VOLTAGE AND CURRENT AS A FUNCTION OF FREQUENCY





**INSULATION RESISTANCE**



**APPLICATION NOTES**

- For X2 electromagnetic interference suppression in **across the line applications** (50/60 Hz) with a maximum mains voltage of 275 V (AC).
- These capacitors are not intended for continuous pulse applications. For these situations, capacitors of the AC and pulse programs must be used.
- These capacitors are not intended for series impedance application. For these situations in case safety approvals are requested, please refer to our special capacitors of 1772 series with internal series connection.
- The maximum ambient temperature must not exceed 110 °C.
- Rated voltage pulse slope:  
If the pulse voltage is lower than the rated voltage, the values of the specific reference data can be multiplied by 385 V (DC) and divided by the applied voltage.

**INSPECTION REQUIREMENTS**

**GENERAL NOTES**

1. Sub-clause numbers of tests and performance requirements refer to the “Sectional Specification, IEC\_publication EN132400 (IEC 60384-14) and Section One of this specification”.
2. In this table: D = destructive  
ND = non-destructive

**Group C inspection requirements**

SUB-CLAUSE NUMBER AND TEST	D OR ND	CONDITIONS	PERFORMANCE REQUIREMENTS
SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1	D		
4.1 Dimensions (detail)  Initial measurements		Capacitance Tangent of loss angle: For C ≤ 1 μF at 10 kHz For C > 1 μF at 1 kHz	As specified in Chapters “General data” of this specification
4.3 Robustness of terminations		Tensile: load 10 N; 10 s Bending: load 5 N; 4 x 90°	No visible damage

Vishay BCcomponents Interference Suppression Film Capacitors  
MKP Radial Potted Type

SUB-CLAUSE NUMBER AND TEST	D OR ND	CONDITIONS	PERFORMANCE REQUIREMENTS
<p>4.4 Resistance to soldering heat</p> <p>4.19 Component solvent resistance</p> <p>4.4.2 Final measurements</p>		<p>No pre-drying Method: 1A Solder bath: 280 °C Duration: 10 s</p> <p>Isopropylalcohol at room temperature Method: 2 Immersion time: 5 ± 0.5 min Recovery time: Min 1 hour, max 2 hours</p> <p>Visual examination</p> <p>Capacitance Tangent of loss angle</p> <p>Insulation resistance</p>	<p>No visible damage Legible marking <math> \Delta C/C  \leq 5\%</math> of the value measured initially. Increase of tan <math>\delta</math>: <math>\leq 0.008</math> for: <math>C \leq 1 \mu\text{F}</math> or <math>\leq 0.005</math> for: <math>C &gt; 1 \mu\text{F}</math> Compared to values measured initially As specified in Section "Insulation Resistance" of this specification</p>
<p><b>SUB-GROUP C1A PART OF SAMPLE OF SUB-GROUP C1</b></p>	<p><b>D</b></p>		
<p>Initial measurements</p> <p>4.20 Solvent resistance of the marking: see Section "General notes"; item 5.</p> <p>4.6 Rapid change of temperature</p> <p>4.6.1 Inspection</p> <p>4.7 Vibration (see note 3.1)</p> <p>4.7.2 Final inspection</p> <p>4.9 Shock (see note 3)</p>		<p>Capacitance Tangent of loss angle: For <math>C \leq 1 \mu\text{F}</math> at 10 kHz For <math>C &gt; 1 \mu\text{F}</math> at 1 kHz</p> <p>Isopropylalcohol at room temperature Method: 1 Rubbing material: cotton wool Immersion time: 5 ± 0.5 min</p> <p><math>\theta A = -55\text{ °C}</math> <math>\theta B = +110\text{ °C}</math> 5 cycles Duration <math>t = 30\text{ min}</math></p> <p>Visual examination Mounting: see Section "Mounting" of this specification Procedure B4 Frequency range: 10 to 55 Hz. Amplitude: 0.75 mm or Acceleration 98 m/s<sup>2</sup> (whichever is less severe) Total duration 6 hours.</p> <p>Visual examination Mounting: see Section "Mounting" for more information Pulse shape: half sine Acceleration: 490 m/s<sup>2</sup> Duration of pulse: 11 ms</p>	<p>No visible damage Legible marking</p> <p>No visible damage</p> <p>No visible damage</p>



Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type


SUB-CLAUSE NUMBER AND TEST	D OR ND	CONDITIONS	PERFORMANCE REQUIREMENTS
4.9.2 Final measurements		Visual examination Capacitance Tangent of loss angle  Insulation resistance	No visible damage $ \Delta C/C  \leq 5\%$ of the value measured initially. Increase of $\tan \delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured initially  As specified in Section "Insulation Resistance" of this specification
<b>SUB-GROUP C1 COMBINED SAMPLE OF SPECIMENS OF SUB-GROUPS C1A AND C1B</b>	<b>D</b>		
4.11 Climatic sequence 4.11.1 Initial measurements  4.11.2 Dry heat 4.11.3 Damp heat cyclic Test Db First cycle 4.11.4 Cold 4.11.5 Damp heat cyclic Test Db remaining cycles 4.11.6 Final measurements		Capacitance Measured in 4.4.2 and 4.9.2 Tangent of loss angle: Measured initially in C1A and C1B Temperature: 110 °C Duration: 16 hours  Temperature: - 55 °C Duration: 2 hours  Visual examination  Capacitance Tangent of loss angle  Voltage proof 1200 V (DC); 1 min between term. Insulation resistance	No visible damage Legible marking $ \Delta C/C  \leq 5\%$ of the value measured in 4.11.1. Increase of $\tan \delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured in 4.11.1. No permanent breakdown or flash-over $\geq 50\%$ of values specified in Section "Insulation resistance" of this specification
<b>SUB GROUP C2</b>	<b>D</b>		
4.12 Damp heat steady state  4.12.1 Initial measurements		56 days; 40 °C; 90 to 95 % RH no load Capacitance Tangent of loss angle: For $C \leq 1 \mu\text{F}$ at 10 kHz or For $C > 1 \mu\text{F}$ at 1 kHz	



Vishay BCcomponents Interference Suppression Film Capacitors  
MKP Radial Potted Type

SUB-CLAUSE NUMBER AND TEST	D OR ND	CONDITIONS	PERFORMANCE REQUIREMENTS
4.12.3 Final measurements		Visual examination  Capacitance Tangent of loss angle   Voltage proof 1200 V (DC); 1 min between term. Insulation resistance	No visible damage Legible marking $ \Delta C/C  \leq 5\%$ of the value measured in 4.12.1. Increase of tan $\delta$ : $\leq 0.008$ for: $C \leq 1 \mu F$ or $\leq 0.005$ for: $C > 1 \mu F$ Compared to values measured in 4.12.1. No permanent breakdown or flash-over $\geq 50\%$ of values specified in Section "Insulation resistance" of this specification
<b>SUB-GROUP C3</b>	<b>D</b>		
4.13.1 Initial measurements  4.13 Impulse voltage  4.14 Endurance  4.14.7 Final measurements		Capacitance Tangent of loss angle: For $C \leq 1 \mu F$ at 10 kHz For $C > 1 \mu F$ at 1 kHz  3 successive impulses, full wave, peak voltage: X2: 2.5 kV for $C \leq 1 \mu F$ X2: 2.5 kV/ $\sqrt{C}$ for $C > 1 \mu F$ Max.24 pulses  Duration: 1000 h 1.25 x $U_{Rac}$ at 110 °C Once in every hour the voltage is increased to 1000 V (RMS) for 0.1 s via resistor of $47 \Omega \pm 5\%$  Visual examination  Capacitance Tangent of loss angle   Voltage proof 1200 V (DC); 1 min between terminations. 2050 V (DC); 1 min between terminations and case.  Insulation resistance	No selfhealing breakdowns or flashover           No visible damage Legible marking $ \Delta C/C  \leq 10\%$ compared to values measured in 4.13.1. Increase of tan $\delta$ : $\leq 0.008$ for: $C \leq 1 \mu F$ or $\leq 0.005$ for: $C > 1 \mu F$ Compared to values measured in 4.13.1. No permanent breakdown or flash-over   $\geq 50\%$ of values specified in Section "Insulation resistance" of this specification

Interference Suppression Film Capacitors Vishay BCcomponents  
MKP Radial Potted Type

SUB-CLAUSE NUMBER AND TEST	D OR ND	CONDITIONS	PERFORMANCE REQUIREMENTS
<b>SUB-GROUP C4</b>	<b>D</b>		
4.15 Charge and discharge  4.15.1 Initial measurements  4.15.3 Final measurements		10 000 cycles (50 c/s) charge to UR half sinewave Duration: 5 ms Discharge resistance: $R = \frac{385 \text{ Vdc}}{1.5 \times C (dU/dt)}$ $R_{\min} = 2.2 \Omega$  Capacitance Tangent of loss angle: For $C \leq 1 \mu\text{F}$ at 10 kHz For $C > 1 \mu\text{F}$ at 1 kHz  Capacitance  Tangent of loss angle    Insulation resistance	$ \Delta C/C  \leq 10 \%$ compared to values measured in 4.15.1. Increase of $\tan \delta$ : $\leq 0.008$ for: $C \leq 1 \mu\text{F}$ or $\leq 0.005$ for: $C > 1 \mu\text{F}$ Compared to values measured in 4.15.1. $\geq 50 \%$ of values specified in Section "Insulation resistance" of this specification
<b>SUB-GROUP C5</b>	<b>D</b>		
4.16 Radio frequency characteristic		Resonance frequency	As specified in Section "Resonant frequency" of this specification. $\pm 10 \%$
<b>SUB-GROUP C6</b>	<b>D</b>		
4.17 Passive flammability Class B		Bore of gas jet: $\varnothing 0.5 \text{ mm}$ Fuel: butane Test duration for actual volume V in mm <sup>3</sup> : V . 250: 10 s 250 < V . 500: 20 s 500 < V . 1750: 30 s V > 1750: 60 s One flame application  	After removing test flame from capacitor, the capacitor must not continue to burn for more than 10 s. No burning particle must drop from the sample.
<b>SUB-GROUP C7</b>			
4.18 Active flammability		20 x 2.5 kV discharges on the test capacitor connected to $U_{\text{Rac}}$	The cheese cloth around the capacitors shall not burn with a flame. No electrical measurements are required.



## Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.