



DC POWER CONNECTORS: KLDHCX Series

High Current PCB Mount DC Locking Type Power Jack

Product Features

- 2.0mm and 2.5mm.
- Built-In DC On/Off Switch
- To Be Used with Locking/Non-locking Tuning Fork Style Plug Laptop and Palm Computers, Portable Modems, Radar Detectors, and Other Portable Device Applications
- CSA/NRTL Certified File No. LR78160
- UL File No. E140125

Performance Specifications

- Materials and Finish
- Plastic Housing:** PBT, UL94V-0 Rated, Black Color
- Center Pin:** Brass, Nickel Plated
- Contact #1:** Brass, Tin Plated
- Contact #2:** Phosphor Bronze, Tin Plated
- Contact #3:** Brass, Tin Plated

Electrical Characteristics

- Rated Current:** 5A
- Rated Voltage:** 24V RMS
- Insulation Resistance:** 50 Megohms Min. at 100 or 200V DC for 1 Minute
- Contact Resistance:** 30 milliohms Max.
- Dielectric Withstanding Voltage:** 250V AC Min. for 1 Minute

Mechanical Characteristics

- Durability Test:** 5000 Cycles
- Insertion Force:** 0.3kg Max.
- Extraction Force:** 0.3kg Min.

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

2D Drawing	IGES	STEP	3D PDF
Solder Profile	CofC RoHS Compliant	CofC REACH Compliant	UL Plastic File
Certificate of Origin	Check Stock	Request a Sample	Send Us An Email

Generated Part Number



Part Number Builder



Series

KLDHCX-0202 - High Current PCB Mount DC Power Jack

Diameter

- A - 2.0mm Center Pin Diameter
- B - 2.5mm Center Pin Diameter

Peg

- Blank - Without Peg
- P - With Peg

Type


LT - Locking Type

Contact Kycon For Other Options

Recommended to be used with Kycon locking plug (tuning fork design):

KLDX-PA-0202-A-LT, KLDX-PA-0202-B-LT

If used with non-locking plug, tuning fork design is required. See picture.



KLDHCX-0202 Series

Dimensions in mm

KLDHCX-0202-x-LT

