

毫米波轉接器 2.4-JJG 2.4MM 公轉公 DC-50G VSWR1.2/50ohm


2.4-JJG

- 1 2.4mm公头-公头
- 2 DC-50G SWR \leq 1.2



产品型号Model: 2.4-JJG

频率Frequency:DC-50GHz



注 Note: 尺寸 Dimensions (mm)

产品参数 Product parameters

1. 电气 Electrical

1.1	阻抗 Impedance	50 Ω
1.2	频率范围 Frequency range	DC-50GHz
1.3	驻波 VSWR	\leq 1.2
1.4	介质耐压 Dielectric withstanding voltage	500V rms
1.5	内导体接触电阻 Internal conductor contact resistance	\leq 4m Ω
1.6	外导体接触电阻 External conductor contact resistance	\leq 2.5m Ω
1.7	绝缘电阻 Insulation resistance	\geq 1000M Ω

2. 环境与机械 Environment and Machinery

2.1	温度范围 Temperature range	-45 $^{\circ}$ ~+165 $^{\circ}$
2.2	耐久性 Durability	500cycles

3. 材料和镀层 Material and Plating

3.1	内导体 Inner conductor	铍铜镀金 Beryllium copper gold plating
3.2	外导体 Outer conductor	不锈钢钝化 Stainless steel passivation
3.3	绝缘体 Insulator	聚醚酰亚胺 PEI