

AD-A8MC3	SMA Jack to SMC Plug 10GHz VSWR 1.2	50Ω															
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Parts</th> <th style="width: 15%;">Material</th> <th style="width: 70%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Body</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Coupling Nut</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Coupling Nut	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Parts	Material	Plating (Micro-inch)															
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Insulator	Teflon																
Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Coupling Nut	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
<p>Weight: 4.41 g</p>																	

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-A8MC3	SMA Jack to SMC Plug 10GHz VSWR 1.2															
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Interface</div> Standard Mechanically Compatible With	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">SMA</th> <th style="width: 50%;">SMC</th> </tr> </thead> <tbody> <tr> <td>MIL-STD-348B</td> <td>MIL-STD-348B</td> </tr> <tr> <td>2.92 &amp; 3.5</td> <td></td> </tr> </tbody> </table>	SMA	SMC	MIL-STD-348B	MIL-STD-348B	2.92 & 3.5										
SMA	SMC															
MIL-STD-348B	MIL-STD-348B															
2.92 & 3.5																
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Electrical Data</div> Impedance Frequency Range VSWR Insertion Loss Insulation Resistance Dielectric Withstanding Voltage (at sea level) Working Voltage (at sea level)	<table style="width: 100%;"> <tbody> <tr> <td style="width: 50%;">50Ω</td> <td style="width: 50%;"></td> </tr> <tr> <td>DC To 10GHz</td> <td></td> </tr> <tr> <td>≤ 1.2 (DC To 10GHz)</td> <td></td> </tr> <tr> <td>≤ 0.1 x √f(GHz) dB</td> <td></td> </tr> <tr> <td>≥ 5000MΩ</td> <td></td> </tr> <tr> <td>750 V rms</td> <td></td> </tr> <tr> <td>250 V rms</td> <td></td> </tr> </tbody> </table>		50Ω		DC To 10GHz		≤ 1.2 (DC To 10GHz)		≤ 0.1 x √f(GHz) dB		≥ 5000MΩ		750 V rms		250 V rms	
50Ω																
DC To 10GHz																
≤ 1.2 (DC To 10GHz)																
≤ 0.1 x √f(GHz) dB																
≥ 5000MΩ																
750 V rms																
250 V rms																
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Mechanical Data</div> Recommended Coupling Nut Torque Coupling Proof Torque Coupling Nut Retention Force Contact Captivation-axial Durability (mating)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">SMA</th> <th style="width: 50%;">SMC</th> </tr> </thead> <tbody> <tr> <td>4 in-lbs</td> <td>2.2 to 3.1 in-lbs</td> </tr> <tr> <td>5.3 in-lbs</td> <td>6.2 in-lbs</td> </tr> <tr> <td>NA</td> <td>≥ 33.72 lbs</td> </tr> <tr> <td>≥ 6.1 lbs</td> <td>≥ 2.25 lbs</td> </tr> <tr> <td>≥ 100</td> <td>≥ 500</td> </tr> </tbody> </table>		SMA	SMC	4 in-lbs	2.2 to 3.1 in-lbs	5.3 in-lbs	6.2 in-lbs	NA	≥ 33.72 lbs	≥ 6.1 lbs	≥ 2.25 lbs	≥ 100	≥ 500		
SMA	SMC															
4 in-lbs	2.2 to 3.1 in-lbs															
5.3 in-lbs	6.2 in-lbs															
NA	≥ 33.72 lbs															
≥ 6.1 lbs	≥ 2.25 lbs															
≥ 100	≥ 500															
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Environmental Data</div> Temperature Range Thermal Shock Moisture Resistance Corrosion RoHS	<table style="width: 100%;"> <tbody> <tr> <td style="width: 50%;">-65°C to +165°C</td> <td style="width: 50%;"></td> </tr> <tr> <td>MIL-STD-202, Method 107, Condition B</td> <td></td> </tr> <tr> <td>MIL-STD-202, Method 206</td> <td></td> </tr> <tr> <td>MIL-STD-202, Method 101, Condition B</td> <td></td> </tr> <tr> <td>Compliant</td> <td></td> </tr> </tbody> </table>		-65°C to +165°C		MIL-STD-202, Method 107, Condition B		MIL-STD-202, Method 206		MIL-STD-202, Method 101, Condition B		Compliant					
-65°C to +165°C																
MIL-STD-202, Method 107, Condition B																
MIL-STD-202, Method 206																
MIL-STD-202, Method 101, Condition B																
Compliant																

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

# AD-A8MC3

