

TRB PL75-47 三同軸連接器 BNC 三同軸 1553B 匯流排三卡口連接器

Product type	Product number	Notes																																																			
TRB Cable Plug	PL75-47		TRB Cable Plug																																																		
<p><i>Built to Last</i> <i>Premium Quality</i> <i>Superior Mechanical</i> <i>Performance</i> <i>Rugged Physical Properties</i> <i>Extreme Reliability</i></p> <p>Features</p> <ul style="list-style-type: none"> • All metallic parts are machined/formed to extremely close tolerances • All bodies are made of top quality brass with bright nickel plated non-tarnish finish • Fully enclosed, heat-treated, beryllium-copper outer conductor spring (not half hard slotted brass) • Heat-treated, beryllium-copper center socket contact with 4mil/0.1016 inch gold plating <p>Signals require protection from extraneous noise through nonsignal carrying shielding. These interfacing connectors must provide contact surfaces isolated from each other, as well as from the outer shield. (twiaxial/triaxial connectors are designed with two (2) concentric contacts that are isolated from each other and the shielding connection.</p> <p>Cable Plug 3-Lug.....PL75-47 D=4.3 TRX179, TRX316, TRC-50-1, TRC-75-1, RG403 3-Lug.....PL75-40 D=6.5 TRX142, TRC-50-2</p>																																																					
<p>MIL-STD-1553B Data Bus General Specifications Guide</p> <table border="1"> <thead> <tr> <th>Characteristic Requirements</th> <th>78SeriesTRC/TRN</th> <th>88SeriesTRC/TRN</th> <th>158SeriesTRC/TRN</th> <th>Non-constant</th> </tr> </thead> <tbody> <tr> <td>Nominal Impedance</td> <td>Non-constant</td> <td>Non-constant</td> <td>Non-constant</td> <td>Non-constant</td> </tr> <tr> <td>Frequency Range</td> <td>0-500 MHz</td> <td>0-500 MHz</td> <td>0-500 MHz</td> <td>0-2 MHz</td> </tr> <tr> <td>Voltage Rating (max.) @ sea level</td> <td>400 VRM</td> <td>500 VRM</td> <td>400 VRM</td> <td>900 VRM</td> </tr> <tr> <td>VRMS Voltage Rating (max.) @ 7000 ft.</td> <td>100 VRMS</td> <td>125 VRMS</td> <td>100 VRMS</td> <td>N/A</td> </tr> <tr> <td>Insulation Resistance</td> <td>5000 MO</td> <td>5000 MO</td> <td>5000 MO</td> <td>5000 MO</td> </tr> <tr> <td>Dielectric Withstanding Voltage (between outer cond. & inter cond.)</td> <td>1200 VRMS</td> <td>1500 VRMS</td> <td>1200 VRMS</td> <td>900 VAC</td> </tr> <tr> <td>Dielectric Withstanding Voltage (between inter. cond. & outer cond.)</td> <td>500 VRMS</td> <td>500 VRMS</td> <td>500 VRMS</td> <td>900 VAC</td> </tr> <tr> <td>RF High Potential Withstanding Voltage (between outer cond. & inter. cond.)</td> <td>800 VRMS</td> <td>100 VRMS</td> <td>500 VRMS</td> <td>900 VAC @ 60 Hz</td> </tr> <tr> <td>RF High Potential Withstanding Voltage (between inter. & outer cond.)</td> <td>200 VRMS @ 5-7.5 MHz</td> <td>350 VRMS @ 5-7.5 MHz</td> <td>125 VRMS</td> <td>N/A</td> </tr> </tbody> </table>				Characteristic Requirements	78SeriesTRC/TRN	88SeriesTRC/TRN	158SeriesTRC/TRN	Non-constant	Nominal Impedance	Non-constant	Non-constant	Non-constant	Non-constant	Frequency Range	0-500 MHz	0-500 MHz	0-500 MHz	0-2 MHz	Voltage Rating (max.) @ sea level	400 VRM	500 VRM	400 VRM	900 VRM	VRMS Voltage Rating (max.) @ 7000 ft.	100 VRMS	125 VRMS	100 VRMS	N/A	Insulation Resistance	5000 MO	5000 MO	5000 MO	5000 MO	Dielectric Withstanding Voltage (between outer cond. & inter cond.)	1200 VRMS	1500 VRMS	1200 VRMS	900 VAC	Dielectric Withstanding Voltage (between inter. cond. & outer cond.)	500 VRMS	500 VRMS	500 VRMS	900 VAC	RF High Potential Withstanding Voltage (between outer cond. & inter. cond.)	800 VRMS	100 VRMS	500 VRMS	900 VAC @ 60 Hz	RF High Potential Withstanding Voltage (between inter. & outer cond.)	200 VRMS @ 5-7.5 MHz	350 VRMS @ 5-7.5 MHz	125 VRMS	N/A
Characteristic Requirements	78SeriesTRC/TRN	88SeriesTRC/TRN	158SeriesTRC/TRN	Non-constant																																																	
Nominal Impedance	Non-constant	Non-constant	Non-constant	Non-constant																																																	
Frequency Range	0-500 MHz	0-500 MHz	0-500 MHz	0-2 MHz																																																	
Voltage Rating (max.) @ sea level	400 VRM	500 VRM	400 VRM	900 VRM																																																	
VRMS Voltage Rating (max.) @ 7000 ft.	100 VRMS	125 VRMS	100 VRMS	N/A																																																	
Insulation Resistance	5000 MO	5000 MO	5000 MO	5000 MO																																																	
Dielectric Withstanding Voltage (between outer cond. & inter cond.)	1200 VRMS	1500 VRMS	1200 VRMS	900 VAC																																																	
Dielectric Withstanding Voltage (between inter. cond. & outer cond.)	500 VRMS	500 VRMS	500 VRMS	900 VAC																																																	
RF High Potential Withstanding Voltage (between outer cond. & inter. cond.)	800 VRMS	100 VRMS	500 VRMS	900 VAC @ 60 Hz																																																	
RF High Potential Withstanding Voltage (between inter. & outer cond.)	200 VRMS @ 5-7.5 MHz	350 VRMS @ 5-7.5 MHz	125 VRMS	N/A																																																	
<p>KEENYOU Zhenjiang Keengyou co.,ltd Tel:0511-88880683/13615278971 Fax:0511-85901586 http://www.jinyoukeji.com E-mail:bj@jinyoukeji.com</p>	<p>PL75-47</p> <p>JY 3.640. Z. 1220</p>	Projection																																																			
		Tag	Unit	Proportion																																																	
		A	mm	1 : 1																																																	
		第 1 张	共 1 张																																																		
Approved: xue.	Checked: zhu.																																																				

勝特力材料 886-3-5773766
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

产品参数

厂家直销·品质非凡

产品信息 / PRODUCT INFORMATION

产品名称 / 三同轴连接器

制作工艺 / 高精数控

接口类型 / SMA公头

射频范围 / DC-66HZ

接触件材质 / 铜镀金

电压驻波比 / ≤ 1.2

