



■ 技术参数 SPECIFICATIONS

- 线数 (Poles) : 2、3、4
- 适用线规 (Applicable wires) : AWG24#~18#
- 适应基板厚度 (Applicable PC board thickness) : 1.6mm
- 温度范围 (Temperature range) : -25°C~85°C
- 额定电压 (Voltage rating) : 250V.Ac/Dc
- 额定电流 (Current rating) : 8A
- 接触电阻 (Contact resistance) : $\leq 0.01\Omega$
- 绝缘电阻 (Insulation resistance) : $\geq 1000M\Omega$
- 耐压 (Withstand voltage) : 1500V.Ac/1min
- 材料 (Material) :
 - 插头 (Plug housing) : 尼龙 (PA66) UL94V-2(0)
 - 插座 (Receptacle housing) : 尼龙 (PA66) UL94V-2(0)
 - 针座 (Wafer) : 尼龙 (PA66) UL94V-2(0)
 - 端子 (Terminal) : 磷青铜 (Phos.bronze Tin/plated)

端子 TERMINAL (8980/大四P)

| 型号 Type | 适用线规 Applicable wires | | 电线外径 O.D of wire ins mm | 数量 Quantity |
|------------|--------------------------|-------|-------------------------------|----------------|
| | mm ² | AWG# | | |
| HX50800-PT | 0.2~0.83 | 24~18 | 1.5~3.0 | 5000PCS/盘 |
| HX50801-RT | 0.2~0.83 | 24~18 | 1.5~3.0 | 5000PCS/盘 |

■ 安装尺寸 MOUNTING MEASUREMENT

| 线数 (Poles) | 额定电压 (Voltage rating) | 额定电流 (Current rating) | 插头 (Plug Housing) | 插座 (Receptacle Housing) | 针座 (Wafer) |
|---------------|-----------------------------|-----------------------------|----------------------------------|----------------------------------|----------------------------------|
| | | | HX50800-PT (8980/大四P) | HX50801-RT (8980/大四P) | |
| 2 | 250V | 8A | HX50800-2P (8981/大四P) | HX50801-2R (8981/大四P) | HX50801-2A (8981/大四P) |
| | | | HX50800-3P (8981/大四P) | HX50801-3R (8981/大四P) | HX50801-3A (8981/大四P) |
| 4 | 250V | 8A | HX50800-4P (8981/大四P) | HX50801-4R (8981/大四P) | HX50801-4A (8981/大四P) |
| | | | | | |

勝特力電材超市-龍山店 886-3-5773766

勝特力電材超市-光復店 886-3-5729570

勝特力电子(上海) 86-21-34970699

勝特力电子(深圳) 86-755-83298787

<http://www.100y.com.tw>