



说明:

1. 特性:

- 额定电压 : 500V AC MIN
- 大针额定电流 : 10A, 20A, 30A, 40A
- 接触阻抗 : 30mΩ MAX.
- 绝缘阻抗 : 3000MΩ MIN. at 500V DC
- 耐电压值 : 1000V AC RMS for 1Minute
- 温度范围 : -55℃ ~ +105℃
- 盐雾时间 : 48H

2. 材料:

- 胶芯 : PBT, rated UL94V-0
- 接触点: 铜合金, 镀金1u-30u
- 铁壳 : SPCC, 前壳镀镍后壳镀锡
- 铜柱 : 铜合金, 镀锡
- 螺丝 : 铁棒, 镀镍

额定电流	∅A	PCB孔∅B
10A	∅1.80	∅2.00
20A	∅2.80	∅3.00
30A	∅3.30	∅3.50
40A	∅3.80	∅4.00

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2

勝特力電材超市-龍山店 886-3-5773766  
 勝特力電材超市-光復店 886-3-5729570  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
<http://www.100y.com.tw>

SCALE: AS SHOWN	UNIT: mm	
DRAWN WAN	06/17/13	DRAWN NAME:
CHECKED CHEN	06/17/13	4W4母直插铆锁
APPROVED CHEN	06/17/13	PRODUCT NO.
DATE	REV. A	FILE NAME:

REV.	DESCRIPTION	DATE
A	ECN-20130617001(WAN)	06/17/13