



P.C.B LAYOUT

- 说明:
- 特性:
 - 额定电压 :500V AC MIN
 - 大针额定电流:10A, 20A, 30A, 40A
 - 接触电阻 :30mΩ MAX.
 - 绝缘电阻 :3000MΩ MIN. at 500V DC
 - 耐电压值 :1000V AC RMS for 1Minute
 - 温度范围 : -55℃+105℃
 - 盐雾时间 : 48H
 - 材料:
 - 胶芯 : PBT, rated UL94V-0
 - 接触点: 铜合金, 镀金1u-30u
 - 铁壳 : SPCC, 前壳镀镍后壳镀锡
 - 支架 : SPCC, 镀镍
 - 鱼叉 : 铜合金, 镀锡
 - 螺丝 : 镀锌 碳钢

额定电流	∅A	PCB孔∅B
10A	∅1.80	∅2.00
20A	∅2.80	∅3.00
30A	∅3.30	∅3.50
40A	∅3.80	∅4.00

UNLESS OTHERWISE SPECIFIED TOLERANCE	
ANG.	±5°
0.	±0.5
.0	±0.3
.00	±0.2

胜特力電材超市-龍山店 886-3-5773766
 胜特力電材超市-光復店 886-3-5729570
 胜特力电子(上海) 86-21-34970699
 胜特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>

SCALE: AS SHOWN	UNIT: mm
DRAWN WAN	06/17/13
CHECKED CHEN	06/17/13
APPROVED CHEN	06/17/13
DATE	06/17/13
SIZE A4	REV. A
DRAWN NAME: 4W4母弯插柳11.6铁支架带鱼叉柳锁	
PRODUCT NO.	
FILE NAME:	

A ECN-20130617001(WAN)

REV.	DESCRIPTION	DATE	SIZE	REV.	FILE NAME:
1			A4	A	