



更改 REV	變更內容 MODIFICATION	日期 DATE	修改 DRAW
B	EN-05-0129	94/01/21	JOAN
C	EN-08-0628	97/06/18	SAN
D	EN-08-0635	97/06/24	SAN

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-54151736
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- NOTES:
 SPECIFICATION:
 1.Current Rating: 3 A
 2.Withstanding Voltage: 1000 VAC (1 Minute)
 3.Insulation Resistance: 5000 Megohms Min.
 4.Contact Resistance: 25 Milliohms Max.
 5.Operating Temperature: -55°C to +105°C

- MATERIAL:
 1.Contact: Brass
 2.Insulator:P.B.T. + 30%(UL94V-0)
 3.Shell:Steel

ORDER INFORMATION:
 DSBRH-F15 XX B406- G
 COMPLY TO RoHS
 01:GOLD FLASH
 02:SELECTIVE GOLD PLATING

DIMENSION IN mm [Inch]		* : Inspection Item	C
TOLERANCE UNLESS OTHERWISE SPECIFIED		◎ : Cp/Cpk and SPC Control Item	名稱 TITLE
.X±0.20	X'±2'	審核 APPROVE	D-SUB 8.89mm FOOTPRINT HIGH DENSITY,R/A
.XX±0.15	.X'±2'	核對 CHECK	案號 FILE NO.
.XXX±	.XX'±	製圖 DRAW	圖號 DWG NO. DSBRH-F15XXB406-G
			角法 PROJ.
			圖號 SHEET 1 / 1
			比例 SCALE 2:1
			更改 REV D