



REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
 Http://www.100y.com.tw

- Note:
1. Material:
 - 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
 - 1.2 Contact: Copper alloy,t=0.25mm
 - 1.3 Shell: Spcc,t=0.40mm,50P Front-shell t=0.60mm
 2. Specification:
 - 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 mΩ Max.
 - 2.4 Insulation resistance: 1000 MΩ Min.
 - 2.5 Total mating force: 9.0 Kgf Max.
 - 2.6 Total unmating force: 1.0 Kgf Min.
 - 2.7 Temperature range: -55°C~85°C

PART NO.	A±0.2	B±0.2	C±0.2	D±0.03	E±0.2	F±0.2
C-14S	43.92	35.99	25.2			29.0
C-24S	54.71	46.79	36.0			39.8
C-36S	67.69	59.74	48.9			53.0
C-50S	82.78	74.85	64.0			68.1

PART NO:		MATERIAL:			
MODEL NO:		FINISH:			
UNIT: mm	SIZE:	COLOR:		PART NAME: CENTRONIC SOLDER (F) ASSEMBLY	
TOLERANCE UNSPECIFIED		DR: YuHong			
.x ±0.3	.xx ±0.20	CHK: Nick			
.xxx ±0.100	ANG. ±1°	APP: Kent		DWG NO: HC-043-01	
				SCALE: 1:1	REV: A0
				SHEET: 1 of 1	