



Pushing Performance

Pneumatic contact male 3,0 mm



Part number	09 14 000 6152
Specification	Pneumatic contact male 3,0 mm
HARTING eCatalogue	https://b2b.harting.com/09140006152

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Contacts
Type of contact	Pneumatic contact
Description of the contact	Without shut-off Straight

Version

Gender	Male
Manufacturing process	Turned contacts

Technical characteristics

Limiting temperature	-40 +80 °C
Operating pressure	≤8 bar
Tube inner diameter	3 mm

Material properties

Material (contacts)	Delrin acetal
Material (seal)	Buna-N
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No

Page 1 / 2 | Creation date 2021-10-01 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



REACH SVHC substances No Specifications and approvals UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 UL / CSA UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 Commercial data 10 Packaging size 10 Net weight 0.754 g
UL / CSA UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076 Commercial data 10
UL / CSA CSA-C22.2 No. 182.3 ECBT8.E235076 Commercial data Packaging size 10
Packaging size 10
Net weight 0.754 g
Country of origin Germany
European customs tariff number 39269097
eCl@ss 27440204 Contact for industrial connectors

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING: 09140006152