



勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)

1. MATERIAL: NYLON 6/6 UL94V-2.  
COLOR: SEE LEGEND (SHEET 2).
2. FINISH: NOT APPLICABLE
3. PRODUCT SPECIFICATION: PS-41995-001
4. PACKAGING: PK-41995-001.
5. THIS PART IS TO BE USED ONLY WITH MINI-FIT JR. SERIES CONNECTORS WITHOUT MOUNTING EARS, PER CHART. SEE SHEET 2.
6. THIS PART CAN BE USED WITH A STANDARD TIE-STRAP GUN.
7. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
8. PART CONFORMS TO CLASS "B" REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002.
9. IF THIS PRODUCT IS STORED IN AN ENVIRONMENT WITH A RELATIVE HUMIDITY OF LESS THAN 50%, MOISTURE MUST BE ADDED. REFER TO TECHNICAL ADVISORY AS-45499-001 FOR INSTRUCTIONS.

REMOVE 20K ADD 8 CKT EC NO: UCP2011-1341 DRWN: JAGUILAR 2010/11/09 CHKD: BELL 2010/11/09 APPR: FSMITH 2010/12/09	QUALITY SYMBOLS ∇=0 ∇=0 ∇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION		
				IN/MM	2:1	METRIC			
				mm    INCH	DRAWN BY	DATE	STRAIN RELIEF FOR MINI-FIT PLUGS AND RECEPTACLES  <b>MOLEX INCORPORATED</b>		
					DMF	1989/05/01			
		4 PLACES ± --- ± ---	CHECKED BY	DATE	MOLEX INCORPORATED SD-41995-***				
		3 PLACES ± --- ± ---	RHR	1989/05/01					
		2 PLACES ± --- ± ---	APPROVED BY	DATE	DOCUMENT NO. SD-41995-***				
		1 PLACE ± --- ± ---	FSMITH	2010/12/09					
		ANGULAR ±1/2°	MATERIAL NO. <b>SEE CHART</b>		SHEET NO. 1 OF 2				
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SIZE C		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

13	12	11	10	9	8	7	6	5	4	3	2	1
PART NO.	ENG. NO.	FOR USE WITH CONNECTOR NO.	CKT. SIZE	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	<div style="border: 2px solid red; padding: 5px; text-align: center;"> <p>勝特力材料 886-3-5753170            勝特力电子(上海) 86-21-34970699            勝特力电子(深圳) 86-755-83298787  <a href="http://www.100y.com.tw">Http://www.100y.com.tw</a></p> </div>				
15-04-0296	41995-6AA	5557-06R* 5559-06P1*	6	.80/20.3	.52/13.2	1.89/48.0	3.25/82.55					
15-04-0343	41995-8AA	5557-08R* 5559-08P1*	8	.97/24.6	.52/13.2	1.89/48.0	4.25/107.9					
15-04-9342	41995-6AB	5557-06R* 5559-06P1*	6	.80/20.3	.52/13.2	1.89/48.0	3.25/82.55					
15-04-9343	41995-8AB	5557-08R* 5559-08P1*	8	.97/24.6	.52/13.2	1.89/48.0	4.25/107.9					

LEGEND:

BASE NUMBER 41995-\*\*\*

CIRCUIT SIZE (2-22)

MATERIAL \*A\* NYLON 6/6, U.L. 94V-2

COLOR \*B\* = BLACK

SEE SHEET 1 EC NO: UCP2011-1341 DRWN: JAGUILAR CHKD: BELL APPR: FSMITH	2010/11/09 2010/11/09 2010/12/09	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE	SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
		▽=0	mm INCH	IN/MM	1:1	METRIC	☉	
		▽=0	4 PLACES ± --- ± ---	DRAWN BY DATE	TITLE	STRAIN RELIEF FOR MINI-FIT PLUGS AND RECEPTACLES <b>MOLEX INCORPORATED</b>		
		▽=0	3 PLACES ± --- ± ---	DMF 1989/05/01	CHECKED BY DATE			
REV	J1	DESCRIPTION	2 PLACES ± --- ± ---	RHR 1989/05/01	MOLEX INCORPORATED SD-41995-*** SHEET NO. 2 OF 2			
			1 PLACE ± --- ± ---	APPROVED BY DATE				
			ANGULAR ±1/2°	FSMITH 2010/12/09	MATERIAL NO. DOCUMENT NO.			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			SIZE C	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				