



勝特力電材超市-龍山店 886-3-5773766  
勝特力電材超市-光復店 886-3-5729570  
勝特力電子(上海) 86-21-34970699  
勝特力電子(深圳) 86-755-83298787  
<http://www.100y.com.tw>

Part Number : 22035025

Series Number : 5267

Product Category : PCB Headers and Receptacles

Product Description : 2.50mm Pitch, Mini-SPOX PCB Header, Single Row, Vertical, Through Hole, Tin Plating, 2 Circuits, Bag, 3.50mm PC Tail Length

Status : Active

Engineering Number : 5267-02A

---

## Documents & Resources

### Drawings

Drawing 022035025\_sd.pdf

### 3D Models and Design Files

2D Drawing DXF 022035025.dxf

2D Drawing DXF (PDF) 022035025.pdf

3D Model 022035025\_stp.zip

### Specifications

Packaging Specification SPK-5267-001-001.pdf


Product Specification 52641001-PS-000.pdf

Product Specification PS-5264-001-001.pdf

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Compliant with Exemption 44   |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Not Contained per D(2024)4144-DC (27 June 2024)                                       |
| EU RoHS            | Compliant per EU 2015/863   |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

|                |   |
|----------------|---|
| Status         | Active  |
| Category       | PCB Headers and Receptacles   |
| Series         | 5267  |
| Description    | 2.50mm Pitch, Mini-SPOX PCB Header, Single Row, Vertical, Through Hole, Tin Plating, 2 Circuits, Bag, 3.50mm PC Tail Length |
| Application    | Signal, Wire-to-Board   |
| Component Type | PCB Header  |
| Product Family | Mini-SPOX Wire-to-Board Connector System  |
| Product Name   | Mini-SPOX   |
| UPC            | 800753591493  |

#### Agency

|     |         |
|-----|---------|
| CSA | LR19980 |
| UL  | E29179  |

#### Electrical

|                               |      |
|-------------------------------|------|
| Current - Maximum per Contact | 3.0A |
| Voltage - Maximum             | 250V |

#### Physical

|                    |         |
|--------------------|---------|
| Breakaway          | No      |
| Circuits (Loaded)  | 2       |
| Circuits (maximum) | 2       |
| Color - Resin      | Natural |

|                                |                |
|--------------------------------|----------------|
| Durability (mating cycles max) | 30             |
| First Mate / Last Break        | No             |
| Flammability                   | 94V-0          |
| Glow-Wire Capable              | No             |
| Guide to Mating Part           | No             |
| Keying to Mating Part          | None           |
| Lock to Mating Part            | Yes            |
| Material - Plating Mating      | Tin            |
| Material - Plating Termination | Tin            |
| Material - Resin               | Nylon          |
| Net Weight                     | 223.020/mg     |
| Number of Rows                 | 1              |
| Orientation                    | Vertical       |
| Packaging Type                 | Bag            |
| PC Tail Length                 | 3.50mm         |
| PCB Locator                    | No             |
| PCB Retention                  | Yes            |
| PCB Thickness - Recommended    | 1.60mm         |
| Pitch - Mating Interface       | 2.50mm         |
| Plating min - Mating           | 4.064µm        |
| Plating min - Termination      | 4.064µm        |
| Polarized to Mating Part       | Yes            |
| Polarized to PCB               | No             |
| Shrouded                       | Fully          |
| Stackable                      | No             |
| Temperature Range - Operating  | -55° to +105°C |
| Termination Interface Style    | Through Hole   |

---

## Mates With / Use With

### Mates with Part(s)

| Description                              | Part Number |
|--|-------------|
| Mini-SPOX Single Row Receptacle Housings | <u>5264</u> |

勝特力電材超市-龍山店 886-3-5773766  
勝特力電材超市-光復店 886-3-5729570  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
<http://www.100y.com.tw>