



产品编号 : 29110062
Product Description : 2.50mm Pitch Mini-Latch Wire-to-Wire Plug Housing, Friction Lock, with Mounting Ears, 6 Circuits, Natural
系列号 : 5240
状态 : New Business Not Supported
Product Category : Connector Housings
工程编号 : 5240-06



文件和资源

产物环境合规

合规

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	New Business Not Supported
类别	Connector Housings
系列	5240
说明	2.50mm Pitch Mini-Latch Wire-to-Wire Plug Housing, Friction Lock, with Mounting Ears, 6 Circuits, Natural
应用	Signal, Wire-to-Wire
产品系列	Mini-Latch Wire-to-Board / Wire-to-Wire Connector System
产品名称	Mini-Latch
UPC	800753617148

机构

CSA	LR19980
UL	E29179

物理

电路数（最多）	6
颜色-树脂	Natural (White)
阻燃性	94V-0
性别	Plug
符合灼热丝规范	否
锁定插接部位	是
净重	1304.900/mg
行数	1
包装形式	Bag
面板安装式	是
间距 - 插配接口	2.50mm
可堆叠的	否
运行温度范围	-40° to +105° C

This document was generated on Jan 02, 2024