




产品编号 : [640021215](#)

Product Description : 2.50mm Pitch, Wire-to-Board Housing, Female, 12 Circuits, UL94HB, Gray with White TPA

系列号 : 64002

状态 : New Business Not Supported

Product Category : Connector Housings



文件和资源

产物环境合规

合规

GADSL/IMDS	Compliant
China RoHS	Not Relevant
EU ELV	Compliant per 2000/53/EC
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

欧盟 RoHS 合格证书

产品详情

常规

状态	New Business Not Supported
----	----------------------------

类别	Connector Housings
系列	64002
说明	2.50mm Pitch, Wire-to-Board Housing, Female, 12 Circuits, UL94HB, Gray with White TPA
应用	Power, Wire-to-Board
产品名称	不适用
UPC	756054579169

物理

电路数（最多）	12
颜色-树脂	Gray, Natural
性别	Receptacle
符合灼热丝规范	否
插接极性	不适用
锁定插接部位	无
材料 - 树脂	Polyester
净重	2.960/g
行数	2
包装形式	Bag
面板安装式	否
间距 - 插配接口	2.50mm
间距 - 终端界面	2.50mm
有极性的插配件	是
端口	1
可堆叠的	否
运行温度范围	-30° to +85° C