



勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

- △ CONTACTS: PHOSPHOR BRONZE
 RECEPTACLE HOUSING & PIN SPACER: UL V-0 RATED POLYESTER LCP, BLACK
 BRACKET: ZINC
- △ POSITION TOLERANCE APPLIES AT TIP ONLY.
- △ CONTACTS: EITHER 0.00076 [.000030] MIN GOLD PLATE FOR A LENGTH OF 3.35 [.132] MIN ON MATING END OR GOLD FLASH OVER PALLADIUM NICKEL PLATE, 0.00076 [.000030] MIN TOTAL FOR A LENGTH OF 3.35 [.132] MIN ON MATING END, 0.00381 [.000150] MIN TIN FOR A LENGTH OF 3.35 [.127] MIN ON OPPOSITE END, ALL OVER 0.00127 [.000050] MIN NICKEL UNDERPLATE ON ENTIRE CONTACT.
 BRACKET: 0.00254 [.000100] MIN NICKEL OVER 0.00508 [.000200] MIN COPPER.
- △ ACTUAL HOLE SIZE USED WILL DEPEND ON TRACE ROUTING REQUIREMENTS BETWEEN HOLES AND CONNECTOR PLACEMENT TECHNIQUE.

**COPYRIGHT 2005
 TYCO ELECTRONICS CORP
 ALL RIGHTS RESERVED**

X	31.11 [1.225]	70.36 [2.770]	84.20 [3.315]	62.23 [2.450]	66.60 [2.622]	68.94 [2.714]	78.23 [3.080]	100	5749084-9
Y	15.24 [.600]	38.61 [1.520]	52.45 [2.065]	30.48 [1.200]	34.85 [1.372]	37.19 [1.464]	46.48 [1.830]	50	5749084-5
PWB PATTERN	G	F	E	D	C	B	A	NO. OF POSN	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. FERNANDEZ-DOCKES 02-15-05	Tyco Electronics Corporation Harrisburg, PA 17105-3608	
DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED:	CHK S. BOLASH 02-15-05	NAME M. WALMSLEY	PRODUCT SPEC
0 PLC ± .13 [0.005]	1 PLC ± .13 [0.005]	2 PLC ± .13 [0.005]	3 PLC ± .13 [0.005]	4 PLC ± .13 [0.005]
ANGLES ± 0° 30'	FINISH	APPLICATION SPEC	SIZE	CAGE CODE
MATERIAL	FINISH	RESTRICTED TO	WEIGHT	DRAWING NO
			A1	00779
			SCALE 4:1	SHEET 1 OF 1
			CUSTOMER DRAWING	REV B

100 POSITION AS SHOWN