

.062" Commercial Pin & Socket Connector **Product Highlights:** Housing

- In-Line Contact Layout
- 3.68 mm Centerline
 2 Positions
 - WWW.100Y.COM.TWn Centerline
 2 Positions

Product Type Features:

- Product Type = Housing
- Connector Line = Commercial Pin and Socket WWW.100Y.COM.TW
- Number of Positions = 2
- Mount = Free Hanging
- Color = Natural
- WWW.100Y.COM.TW Comment = See AMP Guide 65422 for cross references to Industry Standard .062/.093 product. WWW.100Y.COM WWW.100Y.COM.

WWW.100Y.

WWW.100Y.COM.T

Mechanical Attachment:

- Mating Retention = With
- Mating Retention Type = Detent Lock

Electrical Characteristics:

Voltage (VAC) = 250

Body Related Features:

- Centerline (mm [in]) = 3.68 [0.145]
- Contact Diameter (mm [in]) = 1.57 [0.062]

Contact Related Features:

Contact Layout = In-Line Housing Related Features:

VWW.100Y.COM.TW

- Housing Type = Plug
- WW.100Y.COM.TW Housing Flammability Rating = UL 94V-2 WWW.100Y.COM.TW
- Housing Material = Nylon

WWW.100Y.COM.TW WWW.100Y.COM 勝 特 力 材 料 886-3-5753170 胜特力电子(上海) 86-21-34970699 胜特力电子(深圳) 86-755-83298787

Http://www. 100y. com. tw

WWW.100Y.COM.TW

WWW.100Y.C

WWW.100Y.COM.T WWW.1001. WWW.100Y.COM.T WWW.1003 O COPYRIGHT 19 CM 00 P 138 WWW.100Y.CO1 G REVISED PER EC 0G3B-0138-00 30MAY00 LM SR AMP LOGO AND CAVITY NUMBER LOCATED ON EITHER SURFACE. IWW.100Y.COM.TW WWW.100Y.COM.TW WWW.100Y.COM.TW WWW.100Y.COM.TW (OPPOSITE SIDE - OPTIONAL) WWW.100X. WWW.100Y.COM. WWW.101 WWW.100Y.CC 3. 68-()MIN ±0.25 WWW.100Y.C. toM.TW WWW.100Y.C 100Y.COM.TW W.100 Y.C W.100Y.COM.TW WWW.100Y.COM. WWW WWW.100Y.COM.TW WWW.100Y.COM.TW -19. 81 ±0. 25-WWW.100Y.COM. W.100Y.COM.TW WWW.100Y.COM.TW WW.100Y.COM.TW WW.100Y.COM.TW 2. 67 WWW.100Y.COM.TW 3. 68-0.64-WWW.100Y.COL ø2, 79 WWW.100Y.COM.TW ∟ø3, 18 +0, 25 -0, 13 WWW.1001 5, 05-WWW.100Y.COM.TW MATING CONNECTOR INTERFACE TYPICAL PLUG CAVITY SECTION (DIMENSIONS REFERENCE ONLY) 100Y.COM.TW 特力材料886-3-5753170 胜特力电子(上海) 86-21-34970699 WWW.100Y.COM.TW 胜特力电子(深圳) 86-755-83298787 W.100Y.COM.TW

Http://www.100y.com.tw WWW.100Y WWW.100Y.CO.W.7 WWW.100Y.COM.T

WWW.100Y.COM.TW

W.COM.TW

CENVEDSTEN TABLE								
MM	IN	MM	IN	MM	IN			
0.13	. 005	2. 79	. 110	7. 62	. 300			
0. 25	. 010	3.18	. 125	8. 64	. 340			
0.64	. 025	3, 68	. 145	8. 76	. 345			
2. 13	. 084	5. 05	. 199	11. 18	. 440			
2.67	. 105	5, 08	. 200	19, 81	. 780			



			BLA	CK 7	70340-3	
			NATU	RAL 7	70340-1	
			COL	JR .	PART NO	
	CONTROLLED DOCUMENT.	DIN 30MAY00 L. MGEACHIN. Sr. SIK 30MAY00 S. RIDGILL	AMI	AMP Incorporated Harrisburg, PA 17105-3608		
ON ENSIONS:	OPIC ± -	S. RIDGILL PRODUCT SPIC:	WE	PLUG, 2 CIRCUIT,		
$\oplus =$	1 PLC ± - 2 PLC ± - 3 PLC ± 6.13 4 PLC ± -	APPLICATION SPEC	.U62 MIN AND SUCKET SIZE CAGE CODE DRAWING NO RESTRICTED TO			
IATERIAL	FINISH =	WEIGHT	A 1 00779]= 770340	-	
NYLON, UL 94V-2		CUSTOMER DRAWING		5:1	SHEET 1 OF 1 REV	