






勝特力電材超市-龍山店 886-3-5773766
勝特力電材超市-光復店 886-3-5729570
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
<http://www.100y.com.tw>



SECTION A-A



DETAIL B
SCALE 10:1
ALTERNATE CONFIGURATION



DETAIL A

- 1 MATERIAL:
HOUSING- NYLON UL94V-2 (RED).
CONTACTS- 0.30 [.012] THK COPPER ALLOY
PLATING : BRIGHT TIN-LEAD FOR 0.00203[.000080] MIN THK 647000-2 THRU 1-647000-9 OR MATTE TIN 0.00203[.000080] MIN THK. FOR 3-647000-2 THRU 4-647000-9,
- 2 CONTACTS ACCEPT 22 AWG (0.3 - 0.4 mm²) TIN PLATED SOLID,CONCENTRIC FUSED STRANDED, OR CONCENTRIC STRANDED (7 AND 19 STRAND) WIRE WITH 1.52 [.060] MAX INSULATION DIAMETER.
- 3 MATES WITH STANDARD MTA-100 CONNECTORS: OF THE SAME CIRCUIT SIZES WITH SIMILARLY PLATED CONTACTS WITH POLARIZING TABS-CIRCUIT SIZES 4-19 ONLY WITHOUT POLARIZING TABS-CIRCUIT SIZES 2 & 3.
- DOES NOT MATE WITH MTA-100 CONNECTORS: WITH POLARIZING TABS-CIRCUIT SIZES 2 & 3 ONLY. (SEE DETAIL A)
WITH BLOCKED CIRCUITS -ALL CIRCUIT SIZES. NOT RECOMMENDED FOR MATING WITH MTA-100 CONNECTOR WITHOUT POLARIZING TABS. CIRCUIT SIZES 4-19.
- 4 ACCESSORIES:
REPLACEMENT IDC CONTACTS: 647030-1.
COVERS: SEE TABLE
- 5 QUANTITY OF CENTRALLY POSITIONED RAILS VARIES WITH CIRCUIT SIZE. (SEE TABLE)
LOCATION MAY DIFFER FROM EXAMPLE SHOWN.
- 6 DIMENSIONS IN BRACKETS ARE IN INCHES.
- 7 SIMILAR SIZED LOCK AND SINGLE TAB USED OR CIRCUITS 4 & 5.
- 8 QUANTITY OF GUSSET RIBS VARIES WITH CIRCUIT SIZE (SEE TABLE).
LOCATION MAY DIFFER FROM EXAMPLE SHOWN.
- 9 INNER END RAIL PAIR NOT PRESENT FOR CIRCUIT SIZES 2 OR 3.
- 10 CIRCUIT ID MAY APPEAR FULLY NUMBERED OR SHOWING LOCATION 1 ONLY DEPENDING ON CIRCUIT SIZE.
- 11 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN B. LEWIS CHK R. SWING APP'D E. REILES	28APR97 28APR97 28APR97	TE Connectivity	
DIMENSIONS: mm [INCHES]		TOLERANCES UNLESS OTHERWISE SPECIFIED:		NAME	
0 PLC ± -		1 PLC ± -		2 PLC ± 0.20 [.007]	
3 PLC ± -		4 PLC ± -		5 PLC ± -	
ANGLES		FINISH		PRODUCT SPEC	
MATERIAL		1		APPLICATION SPEC	
1		1		SIZE	
CUSTOMER DRAWING		SCALE 5:1		SHEET 1 OF 2	
REV		H		RESTRICTED TO	
A1		00779		647000	

LOC	DIST	REVISIONS					
		#	LT#	DESCRIPTION	DATE	DWN	APVD
CM	00	-	-	SEE SHEET 1	-	-	-

1-640642-9	1-643077-9	4	2	45.72	1.800	48.95	1.927	50.80	2.000	19	4-647000-9
1-640642-8	1-643077-8	4	2	43.18	1.700	46.41	1.827	48.26	1.900	18	4-647000-8
1-640642-7	1-643077-7	4	2	40.64	1.600	43.87	1.727	45.72	1.800	17	4-647000-7
1-640642-6	1-643077-6	4	2	38.10	1.500	41.33	1.627	43.18	1.700	16	4-647000-6
1-640642-5	1-643077-5	4	2	35.56	1.400	38.79	1.527	40.64	1.600	15	4-647000-5
1-640642-4	1-643077-4	4	2	33.02	1.300	36.25	1.427	38.10	1.500	14	4-647000-4
1-640642-3	1-643077-3	4	2	30.48	1.200	33.71	1.327	35.56	1.400	13	4-647000-3
1-640642-2	1-643077-2	2	1	27.94	1.100	31.17	1.227	33.02	1.300	12	4-647000-2
1-640642-1	1-643077-1	2	1	25.40	1.000	28.63	1.127	30.48	1.200	11	4-647000-1
1-640642-0	1-643077-0	2	1	22.86	.900	26.09	1.027	27.94	1.100	10	4-647000-0
640642-9	643077-9	2	1	20.32	.800	23.55	.927	25.40	1.000	9	3-647000-9
640642-8	643077-8	2	0	17.78	.700	21.01	.827	22.86	.900	8	3-647000-8
640642-7	643077-7	0	0	15.24	.600	18.47	.727	20.32	.800	7	3-647000-7
640642-6	643077-6	0	0	12.70	.500	15.93	.627	17.78	.700	6	3-647000-6
640642-5	643077-5	0	0	10.16	.400	13.39	.527	15.24	.600	5	3-647000-5
640642-4	643077-4	0	0	7.62	.300	10.85	.427	12.70	.500	4	3-647000-4
640642-3	643077-3	0	0	5.08	.200	8.31	.327	10.16	.400	3	3-647000-3
-	643077-2	0	0	2.54	.100	5.77	.227	7.62	.300	2	3-647000-2
1-640642-9	1-643077-9	4	2	45.72	1.800	48.95	1.927	50.80	2.000	19	1-647000-9
1-640642-8	1-643077-8	4	2	43.18	1.700	46.41	1.827	48.26	1.900	18	1-647000-8
1-640642-7	1-643077-7	4	2	40.64	1.600	43.87	1.727	45.72	1.800	17	1-647000-7
1-640642-6	1-643077-6	4	2	38.10	1.500	41.33	1.627	43.18	1.700	16	1-647000-6
1-640642-5	1-643077-5	4	2	35.56	1.400	38.79	1.527	40.64	1.600	15	1-647000-5
1-640642-4	1-643077-4	4	2	33.02	1.300	36.25	1.427	38.10	1.500	14	1-647000-4
1-640642-3	1-643077-3	4	2	30.48	1.200	33.71	1.327	35.56	1.400	13	1-647000-3
1-640642-2	1-643077-2	2	1	27.94	1.100	31.17	1.227	33.02	1.300	12	1-647000-2
1-640642-1	1-643077-1	2	1	25.40	1.000	28.63	1.127	30.48	1.200	11	1-647000-1
1-640642-0	1-643077-0	2	1	22.86	.900	26.09	1.027	27.94	1.100	10	1-647000-0
640642-9	643077-9	2	1	20.32	.800	23.55	.927	25.40	1.000	9	647000-9
640642-8	643077-8	2	0	17.78	.700	21.01	.827	22.86	.900	8	647000-8
640642-7	643077-7	0	0	15.24	.600	18.47	.727	20.32	.800	7	647000-7
640642-6	643077-6	0	0	12.70	.500	15.93	.627	17.78	.700	6	647000-6
640642-5	643077-5	0	0	10.16	.400	13.39	.527	15.24	.600	5	647000-5
640642-4	643077-4	0	0	7.62	.300	10.85	.427	12.70	.500	4	647000-4
640642-3	643077-3	0	0	5.08	.200	8.31	.327	10.16	.400	3	647000-3
-	643077-2	0	0	2.54	.100	5.77	.227	7.62	.300	2	647000-2
DUST COVER	STRAIN RELIEF COVERS	QTY OF GUSSET RIBS	QTY OF CENTRAL RAILS	MM	IN	MM	IN	MM	IN	NO. OF CIRCUITS	PART NO
4	ACCESSORIES	8	5	C		B		A			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm [INCHES]

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC

± -
± -
± -
± -
± -

0 PLC
1 PLC
2 PLC
3 PLC
4 PLC

± -
± -
± -
± -
± -

ANGLES

± -

MATERIAL



FINISH



DWN
E. LEWIS
CHK
R. SWING
APVD
E. BEILES

28APR97
28APR97
28APR97

NAME

PRODUCT SPEC
APPLICATION SPEC

WEIGHT

SIZE
A1

CAGE CODE
00779

DRAWING NO
647000

RESTRICTED TO

—

CUSTOMER DRAWING

SCALE
1:1

SHEET
2

OF
2

REV
H

TE Connectivity

MTA-100 POSTED CONNECTOR
ASSEMBLY,CLOSED END,22 AWG,TIN