



REV	MODIFICATION	DATE	DRAW

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

Specification:

Contact Resistance: 30m Ohm Max.
 Insulation Resistance: 1000M Ohm Min. At 500VDC.
 Rated Voltage And Current: 1.5A At 250VAC Minimum.
 Dielectric Withstanding Voltage: 750V AC (rms)
 for 1 Minute(Rev. 1.1).

Durability (Life Test): 1500 Cycles.
 Insertion Force: 35 Newton Maximum.
 Extraction Force: 10 Newton Minimum.

PCB LAYOUT (BOTTOM VIEW)

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	WHITE	1	
2	PIN TERM.	PHOS. BRONZE,T:0.25	GOLD-TIN PLATED	8	Gold:1~3u"; Ni:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	SHELL	BRASS,T:0.3	NICKEL PLATED	1	Ni:80~120u"
4	SPRING CLIP	BRASS,T:0.3	NICKEL PLATED	1	Ni:80~120u"
5	SPEACER	P.E.	NATURAL	2	

DIMENSION IN mm [Inch]		PROD. SPEC.	TITLE	
TOLERANCE UNLESS OTHERWISE SPECIFIED		PKG. SPEC.	DUAL USB A TYPE VERTICAL 8 PIN DIP	
.X± 0.25	X.±	APPROVE Gary	CUSTOMER DRAWING	
.XX± 0.13	.X±	CHECK Jerry	FILE NO.	DWG NO. USBAD-008XXB001-G
.XXX± 0.05	.XX±	DRAW John	SIZE A4	PROJ. SHEET 1 / 1
			SCALE 2:1	REV A

Ordering Information
 USBAD-008 XX B001-G

Contact Area Plating:
 01-Gold Flash.
 05-05u" Gold Plating.
 10-10u" Gold Plating.
 15-15u" Gold Plating.
 30-30u" Gold Plating.