

Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 2-pole; Pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-132

勝特力電材超市-龍山店 886-3-5773766  
勝特力電材超市-光復店 886-3-5729570  
勝特力電子(上海) 86-21-34970699  
勝特力電子(深圳) 86-755-83298787  
<http://www.100y.com.tw>



**Male header (for PCBs); Straight solder pin 1 x 1 mm; 2-pole; Pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; with closed end; Vertical PCB mounting**

Item No.: 734-132



Male header (for PCBs); Straight solder pin 1 x 1 mm; 2-pole; Pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; with closed end; Vertical PCB mounting

## Marking

RoHS ✓  
Compliant

## Business data

Supplier	WAGO
Item no.	734-132
GTIN / EAN	4044918847490
Content	1
Order amount	200
Customer item number	

## Notes

Item description: 1 x 1mm pin cross section allows nominal current up to 10A 100% protected against mismatching  
Coding option available

## Technical data

### Miscellaneous

No. of poles	2
Pin spacing	3.5 mm (0.138 in)
Color	light gray

Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 2-pole; Pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-132


Technical data	
<i>Ratings per</i>	<i>IEC/EN 60664-1</i>
<i>Rated voltage (III / 3) [V]</i>	<i>160 [V]</i>
<i>Rated impulse voltage (III / 3) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (III/2) [V]</i>	<i>160 [V]</i>
<i>Rated impulse voltage (III / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated voltage (II / 2) [V]</i>	<i>320 [V]</i>
<i>Rated impulse voltage (II / 2) [kV]</i>	<i>2.5 [kV]</i>
<i>Rated current [A]</i>	<i>10 [A]</i>
<i>Legend for ratings</i>	<i>(III / 2) Overvoltage category III /</i>
<i>Number of levels</i>	<i>1</i>
<i>Solder pin length [mm]</i>	<i>4.5 [mm]</i>
<i>Drilled hole diameter (tolerance) [mm]</i>	<i>1.4(+ 0.1) [mm]</i>
<i>Material group</i>	<i>I</i>
<i>Insulating material</i>	<i>Polyamide 66 (PA 66)</i>
<i>Flammability class per UL94</i>	<i>V0</i>
<i>Limit temperature range</i>	<i>-60 ... 100 °C</i>
<i>Contact material</i>	<i>Electrolytic copper (Ecu)</i>
<i>Contact plating</i>	<i>tin-plated</i>
<i>Fire load [MJ]</i>	<i>0.011 [MJ]</i>
<i>Weight [g]</i>	<i>0.56 [g]</i>
<i>Width</i>	<i>9.4 mm / 0.37 Inch</i>
<i>Height</i>	<i>14.8 mm / 0.583 Inch</i>
<i>Height from the surface</i>	<i>10.3 mm / 0.406 Inch</i>
<i>Depth</i>	<i>8.5 mm / 0.335 Inch</i>


Printview: Male header (for PCBs); Straight solder pin 1 x 1 mm; 2-pole; Pin spacing 3.5 mm / 0.138 in; 100% protected against mismatching; with closed end; Vertical PCB mounting - Item No.: 734-132

---

#### Images & drawings







#### Address

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Telefon: 0571/887-0

Fax: 0571/887-169

<http://www.wago.com>

© WAGO Kontakttechnik GmbH & Co. KG

Technische Änderungen und Irrtümer vorbehalten.