

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-602/005-000

**Plug With CAGE CLAMP®connection and snap-in flanges for mounting without tools pin spacing 5 mm /
 0.197 in 2 pole**

Packing unit 50 pieces

RoHS compliant

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 2

Cross section [mm²] 0.08 - 4 mm²

Cross section [AWG] 28 - 12 AWG

Connection method CAGE CLAMP®CONNECTION

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 8.384 g

Color grey

Wiring type Front-entry

No. of connection Points 2

No. of potentials 2

Height 24.4 mm

Height 0.961 in

Width	31.3 mm
Width	1.232 in
Depth	40.8 mm
Depth	1.606 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)