

勝 特 力 材 料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-605/002-000

Plug with CAGE CLAMP®connection and fixing flanges for screw or similar mounting types for parallel or perpendicular mounting pin spacing 5 mm / 0.197 in 5 pole

Packing unit 50 pieces

RoHS compliant

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 5

Cross section [mm²] 0.08 - 4 mm²

Cross section [AWG] 28 - 12 AWG

Measured voltage EN 500 V

Measured shock voltage 6 kV

Pollution degree 3

Current intensity EN 32 A

Weight 16.6 g

Color grey

Wiring type Front-entry

No. of connection Points 5

No. of potentials 5

Height 18.3 mm

Height 0.72 in

Width 40.4 mm

Width	1.591 in
Depth	40.2 mm
Depth	1.583 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)