

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-632

Plug with straight solder pin mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 2 pole

Packing unit 200 pieces

RoHS compliant

Strip length from	12 mm
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from	0.197 in
pole count	2
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Measured voltage EN	500 V
Measured shock voltage	4 kV
Pollution degree	2
Weight	2.426 g
Color	grey
Wiring type	Front-entry
No. of connection Points	2
No. of potentials	2
Height	22.2 mm

Height	0.874 in
Width	11.2 mm
Width	0.441 in
Depth	18.3 mm
Depth	0.72 in

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)