

勝 特 力 材 料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-634/004-000

Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 4 pole

Packing unit 50 pieces

RoHS compliant

Product group	18 (X-COM-SYSTEM)
---------------	-------------------

Pin spacing from	5 mm
------------------	------

Pin spacing from	0.197 in
------------------	----------

pole count	4
------------	---

Measured voltage EN	250 V
---------------------	-------

Measured shock voltage	4 kV
------------------------	------

Pollution degree	3
------------------	---

Current intensity EN	32 A
----------------------	------

Measured voltage EN	500 V
---------------------	-------

Measured shock voltage	4 kV
------------------------	------

Pollution degree	2
------------------	---

Weight	5.685 g
--------	---------

Color	grey
-------	------

Wiring type	Front-entry
-------------	-------------

No. of connection Points	4
--------------------------	---

No. of potentials	4
-------------------	---

Height	22.2 mm
--------	---------

Height	0.874 in
--------	----------

Width	34.7 mm
-------	---------

Width	1.366 in
Depth	18.3 mm
Depth	0.72 in

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)