

勝 特 力 材 料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-636/004-000

Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 6 pole

Packing unit 50 pieces

RoHS compliant

Strip length to 7 mm

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 6

Measured voltage EN 250 V

Measured shock voltage 4 kV

Pollution degree 3

Current intensity EN 32 A

Measured voltage EN 500 V

Measured shock voltage 4 kV

Pollution degree 2

Weight 7.546 g

Color grey

Wiring type Front-entry

No. of connection Points 6

No. of potentials 6

Height 22.2 mm

Height 0.874 in

Width	44.7 mm
Width	1.76 in
Depth	18.3 mm
Depth	0.72 in

勝 特 力 材 料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)