

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 769-641/004-000

|                                                                                                            |                   |
|------------------------------------------------------------------------------------------------------------|-------------------|
| Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 11 pole |                   |
| Packing unit 25 pieces                                                                                     |                   |
| RoHS compliant                                                                                             |                   |
| Weight                                                                                                     | 0 g               |
| Measured shock voltage                                                                                     | 4 kV              |
| Measured voltage EN                                                                                        | 500 V             |
| Pollution degree                                                                                           | 2                 |
| Strip length from                                                                                          | mm                |
| Product group                                                                                              | 18 (X-COM-SYSTEM) |
| Pin spacing from                                                                                           | 5 mm              |
| Pin spacing from                                                                                           | 0.197 in          |
| pole count                                                                                                 | 11                |
| Measured voltage EN                                                                                        | 250 V             |
| Measured shock voltage                                                                                     | 4 kV              |
| Pollution degree                                                                                           | 3                 |
| Current intensity EN                                                                                       | 32 A              |
| Color                                                                                                      | grey              |
| Wiring type                                                                                                | Front-entry       |
| No. of connection Points                                                                                   | 11                |
| No. of potentials                                                                                          | 11                |
| Height                                                                                                     | 22.2 mm           |
| Height                                                                                                     | 0.874 in          |

|                    |             |
|--------------------|-------------|
| Width              | 69.7 mm     |
| Width              | 2.744 in    |
| Depth              | 18.3 mm     |
| Depth              | 0.72 in     |
| Customs Tariff No. | 85369010    |
| Country of Origin  | Deutschland |
|                    |             |

勝特力材料 886-3-5753170  
 勝特力电子(上海) 86-21-34970699  
 勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)