

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)



## 769-644/003-000

Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 14 pole

Packing unit 15 pieces

RoHS compliant

Measured shock voltage 4 kV

Strip length to 12 mm

Measured voltage EN 500 V

Pollution degree 2

Product group 18 (X-COM-SYSTEM)

Pin spacing from 5 mm

Pin spacing from 0.197 in

pole count 14

Measured voltage EN 250 V

Measured shock voltage 4 kV

Pollution degree 3

Current intensity EN 32 A

Weight 14.402 g

Color grey

Wiring type Front-entry

No. of connection Points 14

No. of potentials 14

Height 22.2 mm

Height	0.874 in
Width	84.7 mm
Width	3.335 in
Depth	18.3 mm
Depth	0.72 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170  
勝特力电子(上海) 86-21-34970699  
勝特力电子(深圳) 86-755-83298787  
[Http://www.100y.com.tw](http://www.100y.com.tw)