

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)



769-644/004-000

Plug mating direction perpendicular to pcb 1 x 1 mm / 0.039 x 0.039 in pin spacing 5 mm / 0.197 in 14 pole	
Packing unit 15 pieces	
RoHS compliant	
Measured shock voltage	4 kV
Weight	14.802 g
Measured voltage EN	500 V
Pollution degree	2
Strip length to	mm
Product group	18 (X-COM-SYSTEM)
Pin spacing from	5 mm
Pin spacing from pole count	0.197 in 14
Measured voltage EN	250 V
Measured shock voltage	4 kV
Pollution degree	3
Current intensity EN	32 A
Color	grey
Wiring type	Front-entry
No. of connection Points	14
No. of potentials	14
Height	22.2 mm

Height	0.874 in
Width	84.7 mm
Width	3.335 in
Depth	18.3 mm
Depth	0.72 in
Customs Tariff No.	85369010
Country of Origin	Deutschland

勝特力材料 886-3-5753170
勝特力电子(上海) 86-21-34970699
勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)