





Poles	DIM.A	DIM.B
2Y	2.5	5.85
3Y	5.0	8.35
4Y	7.5	10.85
5Y	10.0	13.35
6Y	12.5	15.85
7Y	15.0	18.35
8Y	17.5	20.85
9Y	20.0	23.35
10Y	22.5	25.85
11Y	25.0	28.35
12Y	27.5	30.85
13Y	30.0	33.35
14Y	32.5	35.85
15Y	35.0	38.35
16Y	37.5	40.85



■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG.#28~#22
Applicable Wire: AWG.#28~#22
- ◆ 额定电压: 250V DC/AC(rms)
Rated voltage: 250V DC/AC(rms)
- ◆ 额定电流: 3A (AWG.#22)
Rated Current: 3A (AWG.#22)
- ◆ 耐压值: 1000V AC/minute
Withstand voltage: 1000V AC/min.
- ◆ 工作温度: -25°C ~ +85°C
Working Temp : -25°C ~ +85°C
- ◆ 绝缘电阻: ≥1000 MΩ
Insulation resistance: ≥1000 MΩ
- ◆ 接触电阻: ≤20 mΩ
Contact resistance: ≤20 mΩ

■ 材料 MATERIAL

- ◆ 胶壳: 尼龙66, UL94-V2
Housing: PA66, UL94-V2

勝特力材料 886-3-5753170
 勝特力电子(上海) 86-21-34970699
 勝特力电子(深圳) 86-755-83298787
[Http://www.100y.com.tw](http://www.100y.com.tw)

GENERAL TOLERANCE	
XX. ±0.40	
X. ±0.30	
.X ±0.25	X.* ± 2*
.XX ±0.15	.X.* ± 1*

SCALE:	3:1
UNIT:	mm
SIZE:	A4

DRAWN:	DATE:
CHECK:	DATE:
APPROVE:	DATE:

DOC. NO:	JD-Y-E001
PARTS NO:	XHS-NY

TITLE:	REV.
工程图	A
SHEET:	1/1