



产品编号 : 1300170023

**Product Description** : Mini-Change Field Attachable, Female Connector, 5 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads

系列号 : 130017

状态 : Active

**Product Category** : Circular Industrial Connectors

工程编号 : 1A5000-34



---

## 文件和资源


### 图纸

图纸 [1300170023\\_sd.pdf](#)

---

## 产物环境合规

### 合规

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Contains Lead per D(2023)3788-DC (14 Jun 2023)  |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863   |

### 多部分产品合规性声明

- Eu RoHS
- REACH SVHC
- Low-Halogen

### 多部分行业合规性文件

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

欧盟 RoHS 合格证书

---

## 产品详情

### 常规

|       |  |
|-------|--|
| 状态    | 活动   |
| 类别    | Circular Industrial Connectors   |
| 系列    | 130017   |
| 说明    | Mini-Change Field Attachable, Female Connector, 5 Pole, Cable Range: 5.08-11.43mm Outside Diameter with Internal Threads |
| 认证    | cCSAus certified   |
| IP 等级 | IP67   |
| 产品系列  | Brad Mini-Change Connectors  |
| 产品名称  | Mini-Change  |
| 类型    | Field Attachable Connector   |
| UPC   | 78172553092  |

### 机构

|     |        |
|-----|--------|
| CSA | LR6837 |
|-----|--------|

### 电气

|         |            |
|---------|------------|
| 每触点最大电流 | 8.0A       |
| 电压 - 最大 | 600V AC/DC |

### 物理

|         |                           |
|---------|---------------------------|
| 电缆直径    | 5.08-11.43mm (.200-.450") |
| 耦合类型    | Internal Thread           |
| 诊断/LED  | 否                         |
| 诊断端口    | 否                         |
| 性别      | 女                         |
| 键槽      | Single                    |
| 材料-连接器体 | Nylon                     |
| 材料 - 触头 | Copper Alloy              |

|             |                     |
|-------------|---------------------|
| 材料—连接螺母     | Nickel-plated Brass |
| 材料 - 接合部位电镀 | 金牌                  |
| 净重          | 21.600/g            |
| 方向          | Straight            |
| 极柱          | 5                   |
| 运行温度范围      | -20° C to +80° C    |
| 线径规格 (AWG)  | 15 to 24            |

---

This document was generated on Mar 26, 2024